

# Product datasheet

Specifications



Kaedra - for power outlet - 3 openings - 1 x 12 modules - 340 x 335 mm

13180

Price: 899.47 ZAR

## Main

|                            |                            |
|----------------------------|----------------------------|
| Range                      | Mureva                     |
| Product Name               | Mureva Enclosure           |
| Product Or Component Type  | Weatherproof enclosure     |
| Enclosure Type             | Enclosure for power outlet |
| Mounting Plate Description | Without mounting plate     |

## Complementary

|                                 |                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------|
| Enclosure Mounting              | Surface                                                                               |
| 9 Mm Pitches                    | 24                                                                                    |
| Number Of 18 Mm Modules Per Row | 12                                                                                    |
| Total Number Of 18 Mm Modules   | 12                                                                                    |
| Number Of Horizontal Rows       | 1                                                                                     |
| Electrical Insulation Class     | Double insulation<br>Class II                                                         |
| Number Of Openings Of Interface | 3                                                                                     |
| Number Of Plates                | 1 for push-button controls<br>3 for 65 x 85 power outlets                             |
| Provided Equipment              | 2 wiring strap<br>1 plate for push-button control<br>3 plate for 65 x 85 power outlet |
| Type Of Front Cover             | Transparent                                                                           |
| Power Dissipation In W          | 28 W                                                                                  |
| [In] Rated Current              | 63 A                                                                                  |
| Type Of Rail                    | DIN                                                                                   |
| Number Of Pre-Cutouts Pg Iso    | 17                                                                                    |
| Locking Options Description     | Optional keylock                                                                      |
| Enclosure Material              | Housing: self-extinguishing polymer                                                   |
| Net Weight                      | 2.1 kg                                                                                |
| Base Dimension                  | 90 x 100 mm                                                                           |
| Width                           | 340 mm                                                                                |
| Height                          | 335 mm                                                                                |
| Depth                           | 160 mm                                                                                |
| Internal Depth                  | 91 mm                                                                                 |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|        |                                                             |
|--------|-------------------------------------------------------------|
| Colour | Door: transparent green<br>Enclosure: light grey (RAL 7035) |
|--------|-------------------------------------------------------------|

## Environment

|                                       |                                                                                                                 |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Standards                             | IEC 61439-3<br>IEC 60670<br>EN 62262<br>IEC 60695-2-1<br>EN 50262                                               |
| Fire Resistance                       | 650 °C conforming to IEC 60695-2-1                                                                              |
| Ip Degree Of Protection               | IP65 conforming to IEC 60529                                                                                    |
| Ik Degree Of Protection               | IK09 conforming to EN 50102                                                                                     |
| Environmental Characteristics (Uv)    | UV resistant: class 3 conforming to ISO 4582:2010<br>Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage Category                  | II                                                                                                              |
| Ambient Air Temperature For Operation | -25...40 °C                                                                                                     |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 17.2 cm  |
| Package 1 Width              | 35.7 cm  |
| Package 1 Length             | 35.0 cm  |
| Package 1 Weight             | 2.161 kg |
| Unit Type Of Package 2       | P12      |
| Number Of Units In Package 2 | 36       |
| Package 2 Height             | 80.0 cm  |
| Package 2 Width              | 80.0 cm  |
| Package 2 Length             | 120.0 cm |
| Package 2 Weight             | 90.84 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Lower Impact Materials   Transparency   RoHS/REACH

Resource performance

✓

Minimum Percentage Of Recycled Plastic Content

25

Well-being performance

✓

Rohs Exemption Information

Yes

✓

Halogen Free Product

Certifications & Standards

|                          |                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                     |
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)                                                            |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                         |
| Circularity Profile      | No need of specific recycling operations                                                                              |