

Product datasheet

Specifications



analog input module Modicon Quantum - 8 I Ni / Pt 100. 200. 500. 1000

140ARI03010

⚠ Discontinued on: 31 Dec 2022

⚠ To be end-of-service on: 31 Dec 2030

⚠ To be discontinued

Price: 50,190.63 ZAR

Main

Range Of Product	Modicon Quantum automation platform
Product Or Component Type	Analogue input module

Complementary

Analogue Input Number	8
Input Type	Differential
Addressing Requirement	9 input words
Analogue Input Type	Temperature probe: - 100...450 °C for Pt 100, Pt 200, Pt 500, Pt 1000 Temperature probe: - 200...850 °C for Pt 100, Pt 200, Pt 500, Pt 1000 Temperature probe: - 60...180 °C for Ni 100, Ni 200, Ni 500, Ni 1000 Temperature probe: 0.5 mA for Ni 100, Ni 200, Ni 500, Ni 1000 Temperature probe: 2.5 mA for Pt 100, Pt 200, Ni 100, Ni 200
Analogue Input Resolution	13 bits
Input Impedance	>= 10 MOhm
Absolute Accuracy Error	0.1 °C
Linearity Error	+/- 0.01 % full scale +/- 0.5 °C
Accuracy Drift According To Temperature	+/- 0.5 °C at 25 °C +/- 0.9 °C at 0...60 °C
Isolation Between Channels And Bus	1780 V AC 47...63 Hz for 60 s 2500 V DC for 60 s
Isolation Between Channels	300 Vrms AC
Update Time	1200 ms 3 wires 640 ms 2 wires/4 wires
Fault Type	Broken wire Overtacking scale
Marking	CE
Local Signalling	1 LED (green) for bus communication is present (Active) 1 LED (red) for external fault 8 LEDs (green) for channel is turned on 8 LEDs (red) for channel fault
Bus Current Requirement	200 mA
Power Dissipation In W	1 W
Module Format	Standard
Net Weight	0.3 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	UL 508 CSA C22.2 No 142
Product Certifications	FM Class 1 Division 2 cUL
Resistance To Electrostatic Discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance To Electromagnetic Fields	10 V/m 80...1000 MHz conforming to IEC 801-3
Ambient Air Temperature For Operation	0...60 °C
Ambient Air Temperature For Storage	-40...85 °C
Relative Humidity	95 % without condensation
Operating Altitude	<= 5000 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.7 cm
Package 1 Width	16.5 cm
Package 1 Length	31.4 cm
Package 1 Weight	440.0 g

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes


Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Dimensions Drawings

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots

Connections and Schema

RTD Input 8-Channel Module

Wiring Diagram

