

# Product datasheet

Specifications



ACP control plate. Transferpact. 380 VAC to 415 VAC 50/60Hz. 440 VAC 60Hz

29364

Price: 7,359.17 ZAR

## Main

|                                   |                                                                                                                                                                                                                                                                   |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range Of Product                  | Compact NS630b...1600<br>NSX400...630<br>Compact NS100...630<br>MasterPact NW<br>MasterPact NT<br>NSX100...250                                                                                                                                                    |
| Range                             | ComPact                                                                                                                                                                                                                                                           |
| Product Or Component Type         | Control plate                                                                                                                                                                                                                                                     |
| Accessory / Separate Part Categor | Interlocking accessory                                                                                                                                                                                                                                            |
| Range Compatibility               | ComPact ComPact NS circuit breaker<br>ComPact ComPact NSX circuit breaker<br>Masterpact MasterPact NT circuit breaker<br>Masterpact MasterPact NT switch disconnecter<br>Masterpact MasterPact NW circuit breaker<br>Masterpact MasterPact NW switch disconnecter |
| Device Short Name                 | ACP                                                                                                                                                                                                                                                               |
| [Us] Rated Supply Voltage         | 380...415 V AC at 50/60 Hz<br>440 V AC at 60 Hz                                                                                                                                                                                                                   |

## Complementary

|                       |                                                                                                                |
|-----------------------|----------------------------------------------------------------------------------------------------------------|
| Interlocked Device    | MasterPact NW<br>NSX400...630<br>NSX100...250<br>Compact NS630b...1600<br>Compact NS100...630<br>MasterPact NT |
| Selection Modes       | Circuit breaker on N<br>Circuit breaker on R                                                                   |
| Input Type            | Contacts customer voluntary order to transfer to source R                                                      |
| Output Type           | Contacts customer: indication of operation in automatic or stop mode                                           |
| Product Compatibility | Compact NSX400...630<br>Compact NSX100...250<br>Compact NS630b...1600                                          |

## Environment

|                         |                                                                                                                    |
|-------------------------|--------------------------------------------------------------------------------------------------------------------|
| Ip Degree Of Protection | IP20 connectors: conforming to EN 60529<br>IP40 front: conforming to EN 60529<br>IP30 side: conforming to EN 60529 |
| Ik Degree Of Protection | Front: IK07 conforming to EN 50102                                                                                 |

## Packing Units

|                        |     |
|------------------------|-----|
| Unit Type Of Package 1 | PCE |
|------------------------|-----|

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |           |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 12.4 cm   |
| Package 1 Width              | 16.4 cm   |
| Package 1 Length             | 27.9 cm   |
| Package 1 Weight             | 2.568 kg  |
| Unit Type Of Package 2       | S04       |
| Number Of Units In Package 2 | 6         |
| Package 2 Height             | 30.0 cm   |
| Package 2 Width              | 40.0 cm   |
| Package 2 Length             | 60.0 cm   |
| Package 2 Weight             | 16.174 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

## Well-being performance

|                                                                                                              |                                                                                                                             |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
|  Mercury Free               |                                                                                                                             |
|  Rohs Exemption Information | Yes                                                                                                                         |
| Reach Regulation                                                                                             | <a href="#">REACH Declaration</a>                                                                                           |
| Eu Rohs Directive                                                                                            | Compliant with Exemptions                                                                                                   |
| China Rohs Regulation                                                                                        | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Weee                                                                                                         | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |