

# Product datasheet

Specifications



remote controlled source  
changeover. Transferpact. ACP  
plate and BA controller. 380 VAC to  
415 VAC 50/60Hz. 440 VAC 60Hz

29471

**Price: 23,376.71 ZAR**

## Main

<b>Range Of Product</b>	Compact NS100...630 MasterPact NT NSX400...630 Compact NS630b...1600 MasterPact NW NSX100...250
<b>Product Or Component Type</b>	Interface and control unit
<b>Accessory / Separate Part Category</b>	Interlocking accessory
<b>Range Compatibility</b>	ComPact ComPact NS circuit breaker ComPact ComPact NSX circuit breaker Masterpact MasterPact NT circuit breaker Masterpact MasterPact NW circuit breaker
<b>Device Short Name</b>	ACP + BA
<b>[Us] Rated Supply Voltage</b>	380...415 V AC at 50/60 Hz 440 V AC at 60 Hz

## Complementary

<b>Operating Mode</b>	Automatic operation Stop (both normal and replacement source off) Forced operation on replacement source Forced operation on normal source
<b>Interlocked Device</b>	MasterPact NW MasterPact NT NSX100...250 Compact NS630b...1600 NSX400...630 Compact NS100...630
<b>Selection Modes</b>	Circuit breaker on N Circuit breaker on R
<b>Test Function</b>	By opening the P25M circuit breaker supplying the controller
<b>Complementary Function</b>	Voluntary transfer to replacement source (e.g. energy management commands) Additional contact: transfer to replacement source only if contact is closed
<b>Local Signalling</b>	On Fault trip Off
<b>Input Type</b>	Contacts customer voluntary order to transfer to source R
<b>Output Type</b>	Contacts customer: indication of operation in automatic or stop mode
<b>[Ith] Conventional Free Air Thermal Current</b>	8 A

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>[le] Rated Operational Current</b>	AC-12: 4 A AC 440 V AC-12: 5 A AC 380/415 V AC-12: 8 A AC 110 V AC-12: 8 A AC 220/240 V AC-12: 8 A AC 24 V AC-12: 8 A AC 48 V AC-13: 6 A AC 110 V AC-13: 6 A AC 220/240 V AC-13: 7 A AC 24 V AC-13: 7 A AC 48 V AC-14: 4 A AC 110 V AC-14: 4 A AC 220/240 V AC-14: 5 A AC 24 V AC-14: 5 A AC 48 V AC-15: 3 A AC 220/240 V AC-15: 4 A AC 110 V AC-15: 5 A AC 24 V AC-15: 5 A AC 48 V DC-12: 0.4 A DC 250 V DC-12: 0.6 A DC 110 V DC-12: 2 A DC 48 V DC-12: 8 A DC 24 V DC-13: 2 A AC 24 V
---------------------------------------	--

<b>Product Compatibility</b>	Compact NSX100...250 Compact NS630b...1600 Compact NSX400...630
------------------------------	---

## Environment

<b>Standards</b>	IEC 947-5-1
------------------	-------------

<b>Ip Degree Of Protection</b>	IP20 connectors: conforming to EN 60529 IP40 front: conforming to EN 60529 IP30 side: conforming to EN 60529
--------------------------------	--

<b>Ik Degree Of Protection</b>	Front: IK07 conforming to EN 50102
--------------------------------	------------------------------------

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
-------------------------------	-----

<b>Number Of Units In Package 1</b>	1
-------------------------------------	---

<b>Package 1 Height</b>	12.6 cm
-------------------------	---------

<b>Package 1 Width</b>	16.5 cm
------------------------	---------

<b>Package 1 Length</b>	27.9 cm
-------------------------	---------

<b>Package 1 Weight</b>	3.892 kg
-------------------------	----------

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability


**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

 Mercury Free

---

 Rohs Exemption Information [Yes](#)

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant with Exemptions

---

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

---