

Product datasheet

Specifications



remote control source changeover.
Transferpack. ACP plate and UA
controller. 380 VAC to 415 VAC
50/60 Hz. 440 VAC 60 Hz

29473

Price: 23,420.79 ZAR

Main

Range Of Product	NSX100...250 NSX400...630 MasterPact NT Compact NS100...630 Compact NS630b...1600 MasterPact NW
Product Or Component Type	Interface and control unit
Accessory / Separate Part Categor	Interlocking accessory
Range Compatibility	ComPact ComPact NS circuit breaker ComPact ComPact NSX circuit breaker Masterpact MasterPact NT circuit breaker Masterpact MasterPact NW circuit breaker
Device Short Name	ACP + UA
[Us] Rated Supply Voltage	380...415 V AC at 50/60 Hz 440 V AC at 60 Hz

Complementary

Operating Mode	Forced operation on replacement source Stop (both normal and replacement source off) Automatic operation Forced operation on normal source
Interlocked Device	MasterPact NW NSX400...630 NSX100...250 Compact NS100...630 MasterPact NT Compact NS630b...1600
Selection Modes	Circuit breaker on R Circuit breaker on N
Test Function	By pressing the test button on the front of the controller
Complementary Function	Additional contact: transfer to replacement source only if contact is closed Setting of maximum startup time for the replacement source Forced normal source if replacement source not operational during peak-tariff Selection of type of normal source (single-phase or three-phase) Voluntary transfer to replacement source (e.g. energy management commands)
Local Signalling	Off Fault trip On
Input Type	Contacts customer voluntary order to transfer to source R
Output Type	Contacts customer: indication of operation in automatic or stop mode
[Ith] Conventional Free Air Thermal Current	8 A

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ie] Rated Operational Current	AC-12: 4 A AC 440 V
	AC-12: 5 A AC 380/415 V
	AC-12: 8 A AC 110 V
	AC-12: 8 A AC 220/240 V
	AC-12: 8 A AC 24 V
	AC-12: 8 A AC 48 V
	AC-13: 6 A AC 110 V
	AC-13: 6 A AC 220/240 V
	AC-13: 7 A AC 24 V
	AC-13: 7 A AC 48 V
	AC-14: 4 A AC 110 V
	AC-14: 4 A AC 220/240 V
	AC-14: 5 A AC 24 V
	AC-14: 5 A AC 48 V
	AC-15: 3 A AC 220/240 V
	AC-15: 4 A AC 110 V
	AC-15: 5 A AC 24 V
	AC-15: 5 A AC 48 V
	DC-12: 0.4 A DC 250 V
	DC-12: 0.6 A DC 110 V
	DC-12: 2 A DC 48 V
	DC-12: 8 A DC 24 V
	DC-13: 2 A AC 24 V
Product Compatibility	Compact NSX100...250
	Compact NS630b...1600
	Compact NSX400...630

Environment

Standards	IEC 947-5-1
Ip Degree Of Protection	IP20 connectors: conforming to EN 60529
	IP40 front: conforming to EN 60529
	IP30 side: conforming to EN 60529
Ik Degree Of Protection	Front: IK07 conforming to EN 50102

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	30.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	4.673 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	8
Package 2 Height	75.000 cm
Package 2 Width	80.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	48.744 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information