Product datasheet

Specifications

Green Premium™

Discontinued

switch-disconnector Masterpact NW40HADC-E - 4000 A - 900 V - 4 poles - drawout

48884

Discontinued on: 11 Nov 2021

End-of-service on: 31 Mar 2022

Price: 503,769.94 ZAR

Main

Range	MasterPacT
Product Name	MasterPact NW DC
Product Or Component Type	Switch disconnector
Device Short Name	MasterPact NW40DC-E
Switch-Disconnector Name	MasterPact NW40DC-E
Device Application	Direct current
Poles Description	4P
Network Type	DC
[Ie] Rated Operational Current	4000 A DC 500/900 V
[Ui] Rated Insulation Voltage	1000 V DC conforming to IEC 60947-3
[Uimp] Rated Impulse Withstand Voltage	12 kV conforming to IEC 60947-3
[Ue] Rated Operational Voltage	500/900 V DC conforming to IEC 60947-3
Breaking Capacity Code	HA
Suitability For Isolation	Yes conforming to IEC 60947-3
Contact Position Indicator	Yes
Visible Break	No
Pollution Degree	4 conforming to IEC 60664-1

Complementary

Control Type	Push-button
Mounting Mode	Drawout
Mounting Support	Chassis
Operating Rate	10 cyc/h maximum
Mechanical Durability	10000 cycles without maintenance conforming to IEC 60947-3 20000 cycles with maintenance conforming to IEC 60947-3
Electrical Durability	1000 cycles 900 V DC without maintenance conforming to IEC 60947-3 2000 cycles 500 V DC without maintenance conforming to IEC 60947-3
Connection Pitch	150 mm
Height	352 mm
Width	537 mm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	527 mm

Environment

Standards	IEC 60947-3
Product Certifications	ASTA ASEFA
Ip Degree Of Protection	IP30
Ambient Air Temperature For Operation	-25…70 °C
Ambient Air Temperature For Storage	-35…85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	50 cm
Package 1 Width	50 cm
Package 1 Length	60 cm
Package 1 Weight	48 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency



RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information