

# Product datasheet

Specifications



"ERROR:#N/A"

56173

**Price: 10,263.56 ZAR**

## Main

Range	VigiPacT
Device Short Name	RH99M
Product Or Component Type	Residual current protection relay
Relay Application	Protection relay
Mounting Support	DIN rail
Earth-Leakage Protection Class	Type A
Type Of Setting	Selector
Residual Earth-Leakage Sensitivity Adjustment Type	Adjustable 9 settings
Earth-Leakage Sensitivity	0.03...30 A
Earth-Leakage Time Delay	Instantaneous for 0.03 A Adjustable 9 settings 0...4.5 s for 0.03...30 A
Current Sensors Compatibility	VigiPacT TOA earth leakage current sensor VigiPacT A earth leakage current sensor VigiPacT L earth leakage current sensor
[I <sub>the</sub> ] Conventional Enclosed Thermal Current	8 A
Minimum Load	10 mA at 12 V
[U <sub>s</sub> ] Rated Supply Voltage	220...240 V AC 50/60 Hz 55...110 %
Power Consumption In Va	4 VA
Monitored Distribution System	1000 V - AC at 50/60 Hz (maximum) 1000 V - AC at 400 Hz (maximum)
Earthing System	TN-S TT IT
[U <sub>imp</sub> ] Rated Impulse Withstand Voltage	8 kV
Reset	Manual reset

## Complementary

Test Function	Remote test Local
Monitoring	Electronics (continuous) Power supply (continuous) Relay/sensor link (continuous)
Type Of Measurement	Earth fault current internal measurement, range: 80...100 %
Tamperproof Of Settings	Protected by sealable cover

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Connections - Terminals</b>	<p>Auxiliary power supply: terminal block cable(s) 0.2...2.5 mm<sup>2</sup> flexible AWG 24...AWG 12</p> <p>Auxiliary power supply: terminal block cable(s) 0.2...2.5 mm<sup>2</sup> rigid AWG 24...AWG 12</p> <p>Auxiliary power supply: terminal block cable(s) 0.25...2.5 mm<sup>2</sup> flexible AWG 24...AWG 12</p> <p>Fault: screw terminal cable(s) 0.2...2.5 mm<sup>2</sup> flexible AWG 24...AWG 12</p> <p>Fault: screw terminal cable(s) 0.2...4 mm<sup>2</sup> rigid AWG 24...AWG 12</p> <p>Fault: screw terminal cable(s) 0.25...2.5 mm<sup>2</sup> flexible AWG 24...AWG 12</p> <p>Relay test and fault reset: screw terminal cable(s) 0.14...1 mm<sup>2</sup> flexible AWG 26...AWG 16</p> <p>Relay test and fault reset: screw terminal cable(s) 0.14...1.5 mm<sup>2</sup> rigid AWG 26...AWG 16</p> <p>Relay test and fault reset: screw terminal cable(s) 0.25...0.5 mm<sup>2</sup> flexible AWG 26...AWG 16</p> <p>Sensor: screw terminal cable(s) 0.14...1 mm<sup>2</sup> flexible AWG 26...AWG 16</p> <p>Sensor: screw terminal cable(s) 0.14...1.5 mm<sup>2</sup> rigid AWG 26...AWG 16</p> <p>Sensor: screw terminal cable(s) 0.25...0.5 mm<sup>2</sup> flexible AWG 26...AWG 16</p> <p>Voltage presence: screw terminal cable(s) 0.2...2.5 mm<sup>2</sup> flexible AWG 24...AWG 12</p> <p>Voltage presence: screw terminal cable(s) 0.2...4 mm<sup>2</sup> rigid AWG 24...AWG 12</p> <p>Voltage presence: screw terminal cable(s) 0.25...2.5 mm<sup>2</sup> flexible AWG 24...AWG 12</p>
--------------------------------	---

<b>Wire Stripping Length</b>	<p>Auxiliary power supply: 7 mm for top connection</p> <p>Fault: 8 mm for bottom connection</p> <p>Relay test and fault reset: 5 mm for bottom connection</p> <p>Sensor: 5 mm for top connection</p> <p>Voltage presence: 8 mm for bottom connection</p>
------------------------------	--

<b>Tightening Torque</b>	<p>Auxiliary power supply: 0.6 N.m top</p> <p>Fault: 0.6 N.m bottom</p> <p>Relay test and fault reset: 0.25 N.m bottom</p> <p>Sensor: 0.25 N.m top</p> <p>Voltage presence: 0.6 N.m bottom</p>
--------------------------	--

<b>9 Mm Pitches</b>	6
---------------------	---

<b>Standards</b>	<p>EN/IEC 60947-2 Annex M</p> <p>EN/IEC 60755</p> <p>UL 1053</p> <p>CAN/CSA C22.2 No. 144</p>
------------------	---

<b>Width</b>	54 mm
--------------	-------

<b>Height</b>	81 mm
---------------	-------

<b>Depth</b>	74 mm
--------------	-------

<b>Net Weight</b>	0.3 kg
-------------------	--------

<b>Ip Degree Of Protection</b>	<p>IP40 on front face: conforming to EN/IEC 60529</p> <p>IP30 on side parts: conforming to EN/IEC 60529</p> <p>IP20 on connection terminals: conforming to EN/IEC 60529</p>
--------------------------------	---

<b>Ik Degree Of Protection</b>	IK07 conforming to EN 50102
--------------------------------	-----------------------------

<b>Mechanical Robustness</b>	<p>Fire resistance conforming to IEC 60695-2-1</p> <p>IK protection 2 joules: IK07 conforming to EN 50102</p> <p>Vibrations 13.2...100 Hz: 0.7 g</p> <p>Vibrations 2...13.2 Hz: +/- 1 mm</p>
------------------------------	--

## Environment

<b>Overvoltage Category</b>	IV
-----------------------------	----

<b>Electrical Shock Protection Class</b>	Class II
--	----------

<b>Electromagnetic Compatibility</b>	<p>Conducted and radiated emissions: , B, conforming to CISPR 11</p> <p>Conducted radio-frequency immunity test: , 3, conforming to IEC 61000-4-6</p> <p>Electrostatic discharge immunity test: , 4, conforming to IEC 61000-4-2</p> <p>High-energy conducted susceptibility: , 4, conforming to IEC 61000-4-5</p> <p>Low-energy conducted susceptibility: , 4, conforming to IEC 61000-4-4</p> <p>Radiated susceptibility: , 3, conforming to IEC 61000-4-3</p>
--------------------------------------	--

<b>Relative Humidity</b>	95 % at 55 °C
--------------------------	---------------

<b>Pollution Degree</b>	3 conforming to IEC 60664-1
-------------------------	-----------------------------

<b>Ambient Air Temperature For Operation</b>	-35...70 °C
--	-------------

---

Ambient Air Temperature For Storage -55...85 °C

## Packing Units

---

Unit Type Of Package 1 PCE

---

Number Of Units In Package 1 1

---

Package 1 Height 8.5 cm

---

Package 1 Width 9.0 cm

---

Package 1 Length 7.6 cm

---

Package 1 Weight 276.0 g

---

Unit Type Of Package 2 S03

---

Number Of Units In Package 2 36

---

Package 2 Height 30.0 cm

---

Package 2 Width 30.0 cm

---

Package 2 Length 40.0 cm

---

Package 2 Weight 10.424 kg

## Contractual warranty

---

Warranty 18 months

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 Mercury Free

 Rohs Exemption Information Yes

 Pvc Free

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)