

Product datasheet

Specifications



trip unit MicroLogic 7.0 P.
Compact NS630b to NS1600
drawout. selective and earth-
leakage protections

65295

Price: 109,605.38 ZAR

Main

Range	ComPacT
Range Of Product	ComPacT NS630b...1600 new generation
Product Or Component Type	Trip unit
Trip Unit Name	MicroLogic 7.0 P
Trip Unit Technology	Electronic
Range Compatibility	ComPacT new generation NS630b...1600
Device Application	Distribution
Number Of Poles	3P 4P
Protected Poles Description	4t 3t 3t + N/2
Trip Unit Protection Functions	Selective + earth-leakage protection
Protection Type	for overload protection (long time) for short time short-circuit protection for instantaneous short-circuit protection for earth-leakage protection
Trip Unit Rating	630 A at 50 °C 800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C
Network Type	AC
Network Frequency	50/60 Hz
Circuit Breaker Mounting Mode	Drawout

Complementary

Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable 9 settings
[Ir] Long-Time Protection Pick-Up Adjustment Range	0.4...1 x In
Long-Time Protection Delay Adjustment Type Tr	Adjustable 9 settings
[Tr] Long-Time Protection Delay Adjustment Range	0.7...16.6 s at 7.2 x Ir 0.7...24 s at 6 x Ir 12.5...600 s at 1.5 x Ir
Thermal Memory	20 mn
Short-Time Protection Pick-Up Adjustment Type Isd	Adjustable 9 settings
[Isd] Short-Time Protection Pick-Up Adjustment Range	1.5...10 x Ir

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Short-Time Protection Delay Adjustment Type Tsd	Adjustable
[Tsd] Short-Time Protection Delay Adjustment Range	0...0.4 s I ² t=off 0.1...0.4 s I ² t=on
Instantaneous Protection Pick-Up Adjustment Type Ii	Adjustable 9 settings
[Ii] Instantaneous Protection Pick-Up Adjustment Range	Off 2...15 x In
Earth-Leakage Protection	Integrated
Earth-Leakage Protection Sensitivity Adjustment Type Iōn	Adjustable 9 settings
[Iōn] Earth-Leakage Protection Sensitivity Adjustment Range	0.5...30 A
Earth-Leakage Sensitivity	10 A for class A 30 A for class AC
Earth-Leakage Protection Time Delay Adjustment Type Δt	Adjustable 5 settings
[Δt] Earth-Leakage Protection Time Delay Adjustment Range	60...800 ms
Zone Selective Interlocking Zsi	With
Local Signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Display Type	Digital display
Type Of Measurement	Power meter
Communication Of Data	Measurement readout Protection and alarm settings Maintenance indicators

Environment

Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-40...85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	8.0 cm
Package 1 Length	21.5 cm
Package 1 Weight	318.0 g

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Mercury Free	
✓	RoHS Exemption Information	Yes
✓	Pvc Free	

Certifications & Standards

Reach Regulation	REACH Declaration
Eu RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information