

# Product datasheet

Specifications



## PratiKa wander socket - straight - 63 A - 3P + E - 380...415 V AC - IP67

81482

Price: 1,188.32 ZAR

### Main

|                           |               |
|---------------------------|---------------|
| Range                     | Mureva        |
| Product Or Component Type | Wander socket |
| Device Short Name         | Mureva socket |
| Plug, Socket Category     | Low voltage   |
| Poles Description         | 3P + E        |
| Network Type              | AC            |
| Outlet Standard           | Industrial    |

### Complementary

|                                     |                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| Plug, Socket, Control Station Shape | Straight                                                                          |
| [In] Rated Current                  | 63 A                                                                              |
| [Ue] Rated Operational Voltage      | 380...415 V                                                                       |
| Network Frequency                   | 50/60 Hz                                                                          |
| Ground Lug Clockwise Position       | 6 h                                                                               |
| Plug, Socket Material               | Housing: self-extinguishing engineering polymer                                   |
| Contacts Material                   | Pins: stainless steel<br>Sleeves: nickel plated brass<br>Springs: stainless steel |
| Connections - Terminals             | Captive screws                                                                    |
| Cable Cross Section                 | 6...25 mm²                                                                        |
| Cable Outer Diameter                | 17...31 mm                                                                        |
| Cable Entry                         | Cable gland                                                                       |
| Thread Type                         | Pg 36                                                                             |
| Net Weight                          | 0.742 kg                                                                          |
| Height                              | 110 mm                                                                            |
| Width                               | 110 mm                                                                            |
| Depth                               | 265 mm                                                                            |
| Colour                              | Grey (RAL 7035)                                                                   |
| Voltage Colour                      | Red                                                                               |

### Environment

|           |                            |
|-----------|----------------------------|
| Standards | IEC 60309-2<br>IEC 60309-1 |
|-----------|----------------------------|

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                                 |
|---------------------------------------|-------------------------------------------------|
| Ip Degree Of Protection               | IP67 conforming to IEC 60529                    |
| Ik Degree Of Protection               | IK08 conforming to EN 62262                     |
| Fire Resistance                       | 850 °C conforming to IEC 60695-2-1              |
| Relative Humidity                     | 50 % at 40 °C<br>70 % at 30 °C<br>90 % at 20 °C |
| Ambient Air Temperature For Operation | 35 °C ( 86400 s )<br>-25...40 °C                |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 10.9 cm  |
| Package 1 Width              | 10.9 cm  |
| Package 1 Length             | 26.5 cm  |
| Package 1 Weight             | 752.0 g  |
| Unit Type Of Package 2       | S03      |
| Number Of Units In Package 2 | 10       |
| Package 2 Height             | 30.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 8.007 kg |

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

 Mercury Free

 RoHS Exemption Information   [Yes](#)

## Certifications & Standards

|                          |                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                     |
| Eu Rohs Directive        | Compliant with Exemptions                                                                                             |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                         |
| Circularity Profile      | No need of specific recycling operations                                                                              |