

# Product datasheet

Specifications



## Acti9 centralized control and remote indication - iATLc+s

A9C15409

**Price: 840.02 ZAR**

### Main

Range Of Product	Acti9
Device Short Name	iATLc+s
Product Or Component Type	Centralized control and remote indication auxiliary
Signal Contacts Composition	1 C/O
Signalling Circuit Voltage	24 V AC/DC: 10 mA 12...240 V AC: 50/60 Hz 6 A 12...24 V DC: 6 A 15...240 V AC: 50/60 Hz 2 A 13...24 V DC: 2 A
[Uc] Control Circuit Voltage	24...240 V AC 50/60 Hz

### Complementary

[Ui] Rated Insulation Voltage	440 V
[Uimp] Rated Impulse Withstand Voltage	4 kV
Mounting Mode	Fixed, on right side of TL
Mounting Support	DIN rail
9 Mm Pitches	2
Height	86 mm
Width	18 mm
Depth	71 mm
Colour	White
Connections - Terminals	Tunnel type terminals0.5...4 mm <sup>2</sup> - rigid Tunnel type terminals0.5...4 mm <sup>2</sup> - rigid - with cable end Tunnel type terminals1...4 mm <sup>2</sup> - flexible Tunnel type terminals1...4 mm <sup>2</sup> - flexible - with cable end
Wire Stripping Length	11 mm
Tightening Torque	1 N.m
Range Compatibility	Acti 9 Acti9 iTL iTL Acti 9 Acti9 iTL iTLi Acti 9 Acti9 iTL iTLs
Product Compatibility	ITL (32 A) ITL (16 A)

### Environment

Overvoltage Category	III
Ip Degree Of Protection	IP20 conforming to IEC 60529

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Tropicalisation</b>	2
<b>Relative Humidity</b>	95 % at 55 °C
<b>Ambient Air Temperature For Operation</b>	-20...50 °C
<b>Ambient Air Temperature For Storage</b>	-40...70 °C
<b>Standards</b>	EN/IEC 60669-2-2

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	2.9 cm
<b>Package 1 Width</b>	8 cm
<b>Package 1 Length</b>	9 cm
<b>Package 1 Weight</b>	74 g
<b>Unit Type Of Package 2</b>	BB1
<b>Number Of Units In Package 2</b>	8
<b>Package 2 Height</b>	8.5 cm
<b>Package 2 Width</b>	9.2 cm
<b>Package 2 Length</b>	26.5 cm
<b>Package 2 Weight</b>	651 g
<b>Unit Type Of Package 3</b>	S03
<b>Number Of Units In Package 3</b>	72
<b>Package 3 Height</b>	30 cm
<b>Package 3 Width</b>	30 cm
<b>Package 3 Length</b>	40 cm
<b>Package 3 Weight</b>	6.347 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Plastic Parts Product

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure** [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile** No need of specific recycling operations