

Product datasheet

Specifications



iPRD40r modular surge arrester - 4P - IT - 460V - with remote transfert

A9L40421

Price: 1,661.03 ZAR

Main

Range Of Product	Acti9
Product Name	Acti9 iPRD
Product Or Component Type	Surge arrester with pluggable cartridge
Device Short Name	iPRD40r
Device Application	Distribution
Standards	EN 61643-11:2012 IEC 61643-11:2011
Product Certifications	CE
Poles Description	4P
Remote Signalling	With
Signal Contacts Composition	1 SD (1 C/O)
Surge Arrester Type	Electrical distribution network
Earthing System	IT

Complementary

Surge Arrester Class Type	Type 2
Surge Arrester Technology	MOV
[Ue] Rated Operational Voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
[In] Nominal Discharge Current	Common mode: 15 kA (L/PE) Common mode: 15 kA (N/PE)
[Imax] Maximum Discharge Current	Common mode: 40 kA L/PE Common mode: 40 kA N/PE
[Uc] Maximum Continuous Operating Voltage	Common mode: 460 V L/PE
Maximum [Up] Voltage Protection Level	Common mode <2.2 kV type 2 L/PE Common mode <2.2 kV type 2 N/PE
[Ut] Temporary Overvoltage	337 V L/N 5 s withstand 1455 V L/PE 200 ms safe failure mode 1455 V N/PE 200 ms safe failure mode
[Iscrr] Short-Circuit Current Rating	5 kA 415 V Ph/Ph
Disconnecter Device Type	Associated fuse gG 63 A - Icu 15 kA Associated fuse gG 80 A - Icu 50 kA Associated circuit breaker iC60H 40 A curve C - Icu 15 kA Associated circuit breaker IC60N 40 A curve C - Icu 10 kA Associated circuit breaker NG125H 40 A curve C - Icu 36 kA Associated circuit breaker NG125L 40 A curve C - Icu 50 kA Associated circuit breaker NG125N 40 A curve C - Icu 25 kA
Signalling Circuit Voltage	0.25 A/250 V AC 50/60 Hz

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Mounting Mode	Clip-on (DIN rail)
9 Mm Pitches	8
Height	85 mm
Width	72 mm
Depth	69 mm
Net Weight	450 g
Colour	White (RAL 9003)
[I_{pe}] Ground Residual Current	0.6 mA
Connections - Terminals	Tunnel type terminal (top or bottom) 2.5...25 mm ² rigid Tunnel type terminal (top or bottom) 4...16 mm ² flexible Tunnel type terminal (top or bottom) 4...16 mm ² flexible with ferrule
Wire Stripping Length	14 mm
Tightening Torque	3.5 N.m

Environment

Relative Humidity	5...95 %
Operating Altitude	2000 m
Ambient Air Temperature For Operation	-25...60 °C
Ambient Air Temperature For Storage	-40...85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8 cm
Package 1 Width	8 cm
Package 1 Length	9.2 cm
Package 1 Weight	491 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	3
Package 2 Height	8.5 cm
Package 2 Width	10.4 cm
Package 2 Length	27.6 cm
Package 2 Weight	1.539 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	27
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	14.424 kg

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Reach Free Of Svhc

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)
