

Product datasheet

Specifications



shielded cord set - 40-way terminal -
one end flying leads - for X80 I/O - 3
m

BMXFCW301S

Price: 1,893.30 ZAR

Main

Range Of Product	Modicon X80
Accessory / Separate Part Type	Preformed cordset
Product Compatibility	BMXART0414 BMXART0814
Electrical Connection	1 connector 40 ways module side 1 free end with color-coded flying leads terminal block analogue sensor
Cable Length	3 m

Complementary

Net Weight	0.48 kg
------------	---------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	25.000 cm
Package 1 Length	25.000 cm
Package 1 Weight	382.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	9
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.750 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	144
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	74.708 kg

Contractual warranty

Warranty	18 months
----------	-----------

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations
