

Product datasheet

Specifications



Switch disconnecter ComPacT NSX100NA. 4 poles. 100A. AC22A. AC23A

C104100S

Price: 4,188.50 ZAR

Main

Range	ComPacT new generation
Product Name	ComPacT NSX new generation
Device Short Name	NSX100NA
Product Or Component Type	Switch disconnecter
Device Application	Distribution
Poles Description	4P
[Ith] Conventional Free Air Thermal Current	100 A at 50 °C
[Ie] Rated Operational Current	AC-22A: 100 A AC 50/60 Hz 220...690 V AC-23A: 100 A AC 50/60 Hz 220...690 V DC-22A: 100 A DC 250 V 1 pole DC-22A: 100 A DC 500 V 2 poles in series DC-23A: 100 A DC 250 V 1 pole DC-23A: 100 A DC 500 V 2 poles in series DC-22A: 100 A DC 750 V 3 poles in series DC-23A: 100 A DC 750 V 3 poles in series
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz 750 V DC 3 poles in series 500 V DC 2 poles in series 250 V DC 1 pole
Network Type	AC DC
Suitability For Isolation	Yes conforming to EN/IEC 60947-3
Utilisation Category	AC-22A AC-23A DC-22A DC-23A
Breaking Capacity Code	NA
Contact Position Indicator	Yes
Visible Break	No
Mounting Mode	Fixed
[Icw] Rated Short-Time Withstand Current	1.8 kA during 1 s 1.8 kA during 3 s 0.69 kA during 20 s
[Icm] Rated Short-Circuit Making Capacity	330 kA with upstream protection circuit breaker 2.6 kA switch-disconnector alone
Control Type	Toggle
[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Complementary

Mounting Support	Backplate
Upside Connection	Front
Downside Connection	Front
Connection Pitch	35 mm
Mechanical Durability	50000 cycles
Electrical Durability	AC-22A: 35000 cycles 440 V AC 50/60 Hz In/2 AC-23A: 35000 cycles 440 V AC 50/60 Hz In/2 AC-22A: 20000 cycles 440 V AC 50/60 Hz In AC-23A: 20000 cycles 440 V AC 50/60 Hz In AC-22A: 15000 cycles 690 V AC 50/60 Hz In/2 AC-23A: 15000 cycles 690 V AC 50/60 Hz In/2 AC-22A: 8000 cycles 690 V AC 50/60 Hz In AC-23A: 8000 cycles 690 V AC 50/60 Hz In DC-22A: 10000 cycles 250 V DC In/2 (1 pole) DC-23A: 10000 cycles 250 V DC In/2 (1 pole) DC-22A: 5000 cycles 500 V DC In (2 poles in series) DC-23A: 5000 cycles 500 V DC In (2 poles in series)
Width (W)	140 mm
Height (H)	161 mm
Depth (D)	86 mm
Net Weight	2.2 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product Certifications	CE EAC CCC

Environment

Ip Degree Of Protection	IP40 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 62262
Electrical Shock Protection Class	Class II
Pollution Degree	3 conforming to IEC 60664-1
Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-50...85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	14.4 cm
Package 1 Length	19.0 cm
Package 1 Weight	2.304 kg
Unit Type Of Package 2	S03
Number Of Units In Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

Package 2 Weight

14.214 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Pvc Free

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)