

Product datasheet

Specifications



Auxiliary contact, GoPact MCCB 125/200/250, 1 NO/NC contact type, circuit breaker status OF/SD

G12-25AUX240

Main

Range Of Product	GoPact MCCB
Product Or Component Type	Auxiliary contact
Device Short Name	OF and SD
Device Application	Breaker status monitoring
Range Compatibility	GoPact MCCB 125 GoPact MCCB 200 GoPact MCCB 250
Signal Contacts Composition	1 NO/NC

Complementary

Local Signalling	ON/OFF indication for open/close Trip indicator for voltage release indication Trip indicator for electrical fault
Mounting Mode	By screws
[Ith] Conventional Free Air Thermal Current	6 A
[Ue] Rated Operational Voltage	240 V AC
[Ie] Rated Operational Current	AC-12: 6 A at 12 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 240 V AC 50/60 Hz AC-14: 6 A at 12 V AC 50/60 Hz AC-14: 6 A at 24 V AC 50/60 Hz AC-14: 6 A at 48 V AC 50/60 Hz AC-14: 6 A at 110 V AC 50/60 Hz AC-14: 6 A at 240 V AC 50/60 Hz DC-12: 6 A at 12 V DC DC-12: 5 A at 24 V DC DC-12: 1 A at 48 V DC DC-12: 0.5 A at 110 V DC DC-12: 0.25 A at 220 V DC
Mechanical Durability	10000 cycles
Auxiliary Connection Terminal	Pre-wired 0.5 mm ²
Cable Length	500 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.5 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	4.8 cm
Package 1 Weight	600 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	60
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.041 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	720
Package 3 Height	60 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	56.992 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓	Reach Free Of Svhc	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	
Reach Regulation	REACH Declaration	
Eu Rohs Directive	Compliant EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	