

Product datasheet

Specifications



Auxiliary contacts. TeSys GS. 1 NC. early break. front mounting. for GS2 with front/side handle

GS1AM101

Price: 335.16 ZAR

Main

Range Of Product	TeSys
Device Short Name	GS1AM
Product Or Component Type	Auxiliary contact
Contact Application	O, I and test position signalling
Range Compatibility	TeSys TeSys GS fuse-switch disconnecter FuPact FuPacT GS fuse-switch disconnecter
Contacts Type And Composition	1 NC
Contact Operation	Early-break
[Ith] Conventional Free Air Thermal Current	10 A (at 40 °C)
[Ie] Rated Operational Current	6 A at 120 V AC-15 3 A at 240 V AC-15 1.8 A at 400 V AC-15 1.5 A at 480 V AC-15 2.8 A at 24 V DC-13 1.4 A at 48 V DC-13 0.55 A at 125 V DC-13 0.27 A at 250 V DC-13 0.15 A at 400 V DC-13

Complementary

Mechanical Durability	5 Mcycles
Electrical Durability	1 Mcycles AC-15
Switch Rated Current	30 A 32 A 50 A 60 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A 600 A 630 A 800 A 1250 A
Fuse Type	NFC DIN BS CC J
Type Of Operating Handle	External frontal External right side External left side

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Mounting Location	Front face
-------------------	------------

Net Weight	0.015 kg
------------	----------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	1.5 cm
------------------	--------

Package 1 Width	6 cm
-----------------	------

Package 1 Length	8 cm
------------------	------

Package 1 Weight	13 g
------------------	------

Unit Type Of Package 2	S01
------------------------	-----

Number Of Units In Package 2	10
------------------------------	----

Package 2 Height	15 cm
------------------	-------

Package 2 Width	15 cm
-----------------	-------

Package 2 Length	40 cm
------------------	-------

Package 2 Weight	312 g
------------------	-------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)