


Product datasheet

Specifications



Blown fuse signalling contact.
TeSys GS. 1st C/O. for GS1 GS2
3 poles 630 A. DIN fuse size 3

GS2AF63

Price: 2,365.44 ZAR

Main

Range Of Product	TeSys
Device Short Name	GS2AF
Product Or Component Type	Auxiliary contact
Contact Application	Blown fuse signalling
Contacts Type And Composition	1 C/O
Contact Operation	Instantaneous
[Ith] Conventional Free Air Thermal Current	16 A (at 40 °C)
[Ie] Rated Operational Current	12 A at 24 V DC-13 2 A at 48 V DC-13 3 A at 400 V AC-15 4 A at 230 V AC-15 0.4 A at 220 V DC-13 0.6 A at 110 V DC-13

Complementary

Range Compatibility	TeSys TeSys GS fuse-switch disconnecter
Mechanical Durability	30000 cycles
Electrical Durability	30000 cycles AC-15
Product Compatibility	GS
Poles Description	3P
Switch Rated Current	630 A
Fuse Type	DIN NFC
Fuse Size	3
Net Weight	0.46 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	64.0 g
Unit Type Of Package 2	S01

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Units In Package 2	7
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	673.0 g

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information