Product datasheet

Specifications



MX - voltage release - 220...240 V AC 50Hz - 208…277 V AC 60Hz - for TeSys GV4

GV4AS287

Price: 4,384.88 ZAR

Main

Range	TeSys
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Range Compatibility	TeSys TeSys GV4 TeSys TeSys BV4
Voltage Release Type	Shunt trip release
[Uc] Control Circuit Voltage	277 V AC 60 Hz 220...240 V AC 50 Hz 208...240 V AC 60 Hz

Complementary

[Ui] Rated Insulation Voltage	277 V conforming to IEC 60947-1
Threshold Tripping Voltage	0.7...1.1 Un failsafe opening < 0.7 Un possible opening
Impulse Duration	>= 20 ms
Mounting Mode	Internal mounting
Maximum Inrush Power In Va	6 VA
Maximum Hold-In Power Consumption In Va	10 VA
Mechanical Durability	20000 cycles
Operating Time	< 50 ms
Connections - Terminals	Spring terminals 1 0.5…1.5 mm² - cable stiffness: flexible without cable end
Wire Stripping Length	8 mm

Environment

Quantity Per Set	Set of 1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.5 cm
Package 1 Length	6.1 cm
Package 1 Weight	42.0 g

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	8.8 cm
Package 2 Width	12.9 cm
Package 2 Length	18.5 cm
Package 2 Weight	0.5 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	60
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	3.441 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes

Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information