

Product datasheet

Specifications



EasyPact TVS - auxiliary contact mounted on left hand side - NO+NC

GZ1AN11

Price: 133.66 ZAR

Main

Range Of Product	Easy TeSys Power
Range	Easy TeSys
Product Or Component Type	Auxiliary contact block
Device Short Name	GZ1AN
Connections - Terminals	Screw clamp terminals 1 cable(s) 1...2.5 mm²solid Screw clamp terminals 2 cable(s) 1...2.5 mm²solid Screw clamp terminals 1 cable(s) 0.75...2.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.75...2.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.75...1.5 mm²flexible with cable end Screw clamp terminals 1 cable(s) 0.75...1.5 mm²flexible with cable end

Complementary

Range Compatibility	EasyPact EasyPact TVS GZ1E circuit breaker
Mounting Location	Left side
Auxiliary Contacts Operation	Instantaneous 1 NO + 1 NC
Pole Contact Composition	1 NO + 1 NC
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-1
[Ue] Rated Operational Voltage	48...690 V AC 24...240 V DC
[Ith] Conventional Free Air Thermal Current	6 A
Protection Type	GG fuse 10 A
Mechanical Durability	100000 cycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Rated Operational Power In Va	300 VA at 48 V AC-15 - electrical durability: 70000 cycles 400 VA at 690 V AC-15 - electrical durability: 70000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 70000 cycles 500 VA at 500 V AC-15 - electrical durability: 70000 cycles 650 VA at 440 V AC-15 - electrical durability: 70000 cycles 720 VA at 230...240 V AC-15 - electrical durability: 70000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 70000 cycles
Rated Operational Power In W	120 W at 240 V DC-13 - electrical durability: 70000 cycles 140 W at 110 V DC-13 - electrical durability: 70000 cycles 140 W at 24 V DC-13 - electrical durability: 70000 cycles 180 W at 60 V DC-13 - electrical durability: 70000 cycles 240 W at 48 V DC-13 - electrical durability: 70000 cycles
Height	89 mm
Width	9.3 mm
Depth	66 mm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	0.05 kg
------------	---------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	6.500 cm
Package 1 Length	8.500 cm
Package 1 Weight	43.300 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	9.500 cm
Package 2 Width	9.500 cm
Package 2 Length	15.000 cm
Package 2 Weight	488.000 g
Unit Type Of Package 3	S02
Number Of Units In Package 3	60
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	3.156 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information