

Product datasheet

Specifications



Electronic time delay auxiliary contact block. TeSys K. 1C/O. on delay 1-30s. front. control 24-48 V AC/DC

LA2KT2E

Price: 1,844.99 ZAR

Main

| | |
|---|--|
| Range | TeSys |
| Product Name | TeSys K |
| Product Or Component Type | Time delay auxiliary contact block |
| Device Short Name | LA1 |
| Range Compatibility | TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K |
| Mounting Location | Front |
| Pole Contact Composition | 1 C/O |
| Contacts Operation | Time delay |
| Timer Type | On delay |
| Time Delay Range | 1...30 s |
| [Ue] Rated Operational Voltage | 24...48 V AC/DC for control circuit 240 V AC for signalling circuit |
| Rated Operational Voltage Limits | 0.85...1.1 Uc |
| [Ith] Conventional Free Air Thermal Current | 2 A for signalling circuit |
| Standards | EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 |
| Product Certifications | UL CSA CE UKCA |

Complementary

| | |
|-------------------------|---|
| Insulation Resistance | > 10 MOhm |
| Connections - Terminals | Slip-on terminals |
| Reset Time | 1.5 s during time delay 0.5 s after time delay |
| Height | 27 mm |
| Width | 38 mm |
| Depth | 38 mm |
| Net Weight | 0.04 kg |

Environment

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| | |
|--|------------------------------|
| Environmental Characteristic | Normal environment |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
| Protective Treatment | TC conforming to IEC 60068 |
| Ambient Air Temperature For Operation | -10...60 °C |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.000 cm |
| Package 1 Width | 4.800 cm |
| Package 1 Length | 4.800 cm |
| Package 1 Weight | 40.000 g |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 70 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 3.110 kg |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile No need of specific recycling operations