Product datasheet

Specifications



EasyPact TVS - time delay - on delay - 1 NO + 1 NC

LAETSD

Price: 612.40 ZAR

Main

Range	Easy TeSys
Range Of Product	Easy TeSys Control
Product Or Component Type	Time delay auxiliary
Device Application	Signalling
Device Short Name	LAET
Colour	Grey (RAL 7011)

Complementary

Range Compatibility	EasyPact EasyPact TVS LC1E
Mounting Location	Front
Auxiliary Contacts Operation	On-delay contact
Pole Contact Composition	1 NO + 1 NC
[Ui] Rated Insulation Voltage	690 V - for control circuit conforming to IEC 60947-5-1
[Ue] Rated Operational Voltage	<= 690 V
[Ith] Conventional Free Air Thermal Current	8 A (at 60 °C)
Irms Rated Making Capacity	140 A AC conforming to IEC 60947-5-1
[Icw] Rated Short-Time Withstand Current	100 A - 1 s 120 A - 500 ms 140 A - 100 ms
Protection Type	GG fuse 10 A
Mechanical Durability	10 Mcycles
Minimum Switching Current	5 mA
Minimum Switching Voltage	17 V
Non-Overlap Time	1.5 ms on energisation no overlap between NC and NO contact 1.5 ms on de-energisation no overlap between NC and NO contact
Time Delay Range	1...30 s
Insulation Resistance	> 10 MOhm
Connections - Terminals	Control circuit: screw clamp terminals 1 1 mm² - external diameter: 6 mm - cable stiffness: solid or flexible with cable end Control circuit: screw clamp terminals 1 1 mm² - external diameter: 6 mm - cable stiffness: solid or flexible without cable end Control circuit: screw clamp terminals 2 2.5 mm² - external diameter: 6 mm - cable stiffness: solid or flexible with cable end Control circuit: screw clamp terminals 2 2.5 mm² - external diameter: 6 mm - cable stiffness: solid or flexible without cable end
Net Weight	0.06 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Environmental Characteristic	Standard environment
Standards	IEC 60947-5-1
Product Certifications	GOST
Ip Degree Of Protection	IP20 conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Operation	-5…55 °C
Ambient Air Temperature For Storage	-60…80 °C
Operating Altitude	3000 m without derating

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	5.200 cm
Package 1 Length	4.800 cm
Package 1 Weight	82.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	140
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	12.097 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency



RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations