

# Product datasheet

Specifications



## TeSys D contactor - 4P(4 NO) - AC-1 - <= 440 V 60 A - 48 V AC 50/60 Hz coil

LC1DT60AE7

Price: 4,623.11 ZAR

### Main

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| Range                          | TeSys<br>TeSys Deca                                                  |
| Range Of Product               | TeSys Deca                                                           |
| Product Or Component Type      | Contactor                                                            |
| Device Short Name              | LC1D                                                                 |
| Contactor Application          | Resistive load                                                       |
| Utilisation Category           | AC-1                                                                 |
| Poles Description              | 4P                                                                   |
| [Ue] Rated Operational Voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC |
| [Ie] Rated Operational Current | 60 A (at <60 °C) at <= 440 V AC AC-1 for power circuit               |
| [Uc] Control Circuit Voltage   | 48 V AC 50/60 Hz                                                     |

### Complementary

|                                             |                                                                                                                                                                                                                                                                                       |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility Code                          | LC1D                                                                                                                                                                                                                                                                                  |
| Pole Contact Composition                    | 4 NO                                                                                                                                                                                                                                                                                  |
| Protective Cover                            | With                                                                                                                                                                                                                                                                                  |
| [Ith] Conventional Free Air Thermal Current | 10 A (at 60 °C) for signalling circuit<br>60 A (at 60 °C) for power circuit                                                                                                                                                                                                           |
| Irms Rated Making Capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>800 A at 440 V for power circuit conforming to IEC 60947                                                                                                |
| Rated Breaking Capacity                     | 800 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                              |
| [Icw] Rated Short-Time Withstand Current    | 320 A 40 °C - 10 s for power circuit<br>720 A 40 °C - 1 s for power circuit<br>72 A 40 °C - 10 min for power circuit<br>165 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit |
| Associated Fuse Rating                      | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>80 A gG at <= 690 V coordination type 1 for power circuit<br>80 A gG at <= 690 V coordination type 2 for power circuit                                                                                                  |
| Average Impedance                           | 1.6 mOhm - Ith 60 A 50 Hz for power circuit                                                                                                                                                                                                                                           |
| Power Dissipation Per Pole                  | 5.8 W AC-1                                                                                                                                                                                                                                                                            |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[Ui] Rated Insulation Voltage</b>                 | Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified<br>Power circuit: 690 V conforming to IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Overvoltage Category</b>                          | III                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Pollution Degree</b>                              | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>[Uimp] Rated Impulse Withstand Voltage</b>        | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Safety Reliability Level</b>                      | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Mechanical Durability</b>                         | 6 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Electrical Durability</b>                         | 1.4 Mcycles 60 A AC-1 at $U_e \leq 440$ V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Control Circuit Type</b>                          | AC at 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Coil Technology</b>                               | Without built-in suppressor module                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Control Circuit Voltage Limits</b>                | 0.3...0.6 $U_c$ (-40...70 °C):drop-out AC 50/60 Hz<br>0.8...1.1 $U_c$ (-40...60 °C):operational AC 50 Hz<br>0.85...1.1 $U_c$ (-40...60 °C):operational AC 60 Hz<br>1...1.1 $U_c$ (60...70 °C):operational AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Inrush Power In <math>V_a</math></b>              | 140 VA 60 Hz cos phi 0.75 (at 20 °C)<br>160 VA 50 Hz cos phi 0.75 (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Hold-In Power Consumption In <math>V_a</math></b> | 13 VA 60 Hz cos phi 0.3 (at 20 °C)<br>15 VA 50 Hz cos phi 0.3 (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Heat Dissipation</b>                              | 4...5 W at 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Operating Time</b>                                | 4...19 ms opening<br>12...26 ms closing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Maximum Operating Rate</b>                        | 3600 cyc/h 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Connections - Terminals</b>                       | Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminal 1 1...35 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: screw clamp terminal 2 1...25 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: screw clamp terminal 1 1...35 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminal 2 1...25 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminal 1 1...35 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminal 2 1...25 mm <sup>2</sup> - cable stiffness: solid without cable end |

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tightening Torque             | Control circuit: 1.7 N.m - on EverLink BTR screw connectors - with screwdriver flat Ø 6 mm<br>Control circuit: 1.7 N.m - on EverLink BTR screw connectors - with screwdriver Philips No 2<br>Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 25...35 mm² hexagonal screw head 4 mm<br>Power circuit: 5 N.m - on EverLink BTR screw connectors - cable 1...25 mm² hexagonal screw head 4 mm<br>Control circuit: 1.7 N.m - on EverLink BTR screw connectors - with screwdriver pozidriv No 2<br>Power circuit: 2.5 N.m - on EverLink BTR screw connectors - with screwdriver pozidriv No 2 |
| Auxiliary Contact Composition | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Auxiliary Contacts Type       | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Signalling Circuit Frequency  | 25...400 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Minimum Switching Voltage     | 17 V for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Minimum Switching Current     | 5 mA for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Insulation Resistance         | > 10 MOhm for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Non-Overlap Time              | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mounting Support              | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## Environment

|                                                       |                                                                                                                                                                                        |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                             | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>IEC 60335-1                                                                             |
| Product Certifications                                | RINA<br>GL<br>DNV<br>CSA<br>BV<br>LROS (Lloyds register of shipping)<br>GOST<br>UL<br>CCC                                                                                              |
| Ip Degree Of Protection                               | IP20 front face conforming to IEC 60529                                                                                                                                                |
| Protective Treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                        |
| Climatic Withstand                                    | conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat                                                                     |
| Permissible Ambient Air Temperature Around The Device | -40...60 °C<br>60...70 °C with derating                                                                                                                                                |
| Operating Altitude                                    | 0...3000 m                                                                                                                                                                             |
| Fire Resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                     |
| Flame Retardance                                      | V1 conforming to UL 94                                                                                                                                                                 |
| Mechanical Robustness                                 | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Vibrations contactor closed (4 Gn, 5...300 Hz)<br>Shocks contactor closed (15 Gn for 11 ms)<br>Shocks contactor open (10 Gn for 11 ms) |
| Height                                                | 122 mm                                                                                                                                                                                 |
| Width                                                 | 70 mm                                                                                                                                                                                  |
| Depth                                                 | 120 mm                                                                                                                                                                                 |

|            |         |
|------------|---------|
| Net Weight | 1.09 kg |
|------------|---------|

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 7.8 cm   |
| Package 1 Width              | 13.5 cm  |
| Package 1 Length             | 15.2 cm  |
| Package 1 Weight             | 1.087 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

|   |                            |     |
|---|----------------------------|-----|
| ✓ | Reach Free Of Svhc         |     |
| ✓ | Toxic Heavy Metal Free     |     |
| ✓ | Mercury Free               |     |
| ✓ | Rohs Exemption Information | Yes |
| ✓ | Pvc Free                   |     |

## Certifications & Standards

|                          |                                                                                                                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                           |
| Eu Rohs Directive        | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                               |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | <a href="#">End of Life Information</a>                                                                                     |