

# Product datasheet

Specifications



## EasyPact TVS contactor 3P(3 NO) - AC-3 - <= 440 V 200A - 24 V AC coil

LC1E200B5

Price: 5,347.50 ZAR

### Main

|                                |                                                                                                                    |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Range                          | Easy TeSys                                                                                                         |
| Range Of Product               | Easy TeSys Control                                                                                                 |
| Product Or Component Type      | Contactor                                                                                                          |
| Device Short Name              | LC1E                                                                                                               |
| Contactor Application          | Resistive load<br>Motor control                                                                                    |
| Utilisation Category           | AC-1<br>AC-3                                                                                                       |
| Poles Description              | 3P                                                                                                                 |
| [Ue] Rated Operational Voltage | Power circuit: <= 690 V AC 50/60 Hz                                                                                |
| [Ie] Rated Operational Current | 200 A (at <55 °C) at <= 440 V AC AC-3 for power circuit<br>250 A (at <40 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] Control Circuit Voltage   | 24 V AC 50 Hz                                                                                                      |

### Complementary

|                                             |                                                                                                                                                                                                                                                  |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor Power Kw                              | 55 kW at 220...230 V AC 50/60 Hz (AC-3)<br>90 kW at 380...400 V AC 50/60 Hz (AC-3)<br>100 kW at 415 V AC 50/60 Hz (AC-3)<br>100 kW at 440 V AC 50/60 Hz (AC-3)<br>110 kW at 500 V AC 50/60 Hz (AC-3)<br>110 kW at 660...690 V AC 50/60 Hz (AC-3) |
| Pole Contact Composition                    | 3 NO                                                                                                                                                                                                                                             |
| [Ith] Conventional Free Air Thermal Current | 250 A (at 55 °C)                                                                                                                                                                                                                                 |
| Irms Rated Making Capacity                  | 2000 A at 440 V AC for power circuit conforming to IEC 60947-4-1                                                                                                                                                                                 |
| Rated Breaking Capacity                     | 1600 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                        |
| [Icw] Rated Short-Time Withstand Current    | 1500 A 40 °C - 10 s for power circuit                                                                                                                                                                                                            |
| Associated Fuse Rating                      | 10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1<br>315 A gG at <= 690 V coordination type 1 for power circuit                                                                                            |
| Average Impedance                           | 0.33 mOhm - Ith 250 A 50 Hz for power circuit                                                                                                                                                                                                    |
| Power Dissipation Per Pole                  | 13 W AC-3<br>21 W AC-1                                                                                                                                                                                                                           |
| [Ui] Rated Insulation Voltage               | 690 V conforming to IEC 60947-4-1                                                                                                                                                                                                                |
| Overvoltage Category                        | III                                                                                                                                                                                                                                              |
| Pollution Degree                            | 3                                                                                                                                                                                                                                                |
| [Uimp] Rated Impulse Withstand Voltage      | 8 kV coil not connected to the power circuit conforming to IEC 60947                                                                                                                                                                             |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mechanical Durability           | 5000000 cycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Electrical Durability           | 500000 cycles AC-3<br>200000 cycles AC-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Control Circuit Type            | AC at 50 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Control Circuit Voltage Limits  | 0.85...1.1 Uc (-5...55 °C):operational 50 Hz<br>0.35...0.55 Uc (-5...55 °C):drop-out 50 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Inrush Power In Va              | 805 VA 50 Hz cos phi 0.3 (at 20 °C)<br>970 VA 60 Hz cos phi 0.3 (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Hold-In Power Consumption In Va | 55 VA 50 Hz cos phi 0.3 (at 20 °C)<br>66 VA 60 Hz cos phi 0.3 (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Heat Dissipation                | 18...24 W for control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Operating Time                  | 20...35 ms on closing<br>7...15 ms on opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Maximum Operating Rate          | 1200 cyc/h 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Connections - Terminals         | Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 1 1...2.5 mm² - cable stiffness: flexible with cable end<br>Power circuit: cable with lug - external diameter: 150 mm<br>Power circuit: bars 2 - busbar cross section: 3 x 25 mm |
| Tightening Torque               | Control circuit: 1.2 N.m<br>Power circuit: 18 N.m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Minimum Switching Voltage       | 17 V for control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Minimum Switching Current       | 5 mA for control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Insulation Resistance           | > 10 MOhm for control circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Non-Overlap Time                | 1.5 ms on energisation guaranteed between NC and NO contact<br>1.5 ms on de-energisation guaranteed between NC and NO contact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Mounting Support                | Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Environment

|                                                       |                                                                                                                                                                                        |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                             | IEC 60947-4-1<br>IEC 60947-5-1<br>IEC 60947-1                                                                                                                                          |
| Product Certifications                                | EAC<br>CE                                                                                                                                                                              |
| Ip Degree Of Protection                               | IP2X conforming to IEC 60529                                                                                                                                                           |
| Protective Treatment                                  | TH (pollution degree 3) conforming to IEC 60068-2-30 test Db                                                                                                                           |
| Permissible Ambient Air Temperature Around The Device | -20...70 °C at Uc<br>-60...80 °C storage<br>-5...55 °C operation                                                                                                                       |
| Operating Altitude                                    | 3000 m without derating                                                                                                                                                                |
| Fire Resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                     |
| Mechanical Robustness                                 | Vibrations contactor open (1.5 Gn, 5...300 Hz)<br>Vibrations contactor closed (3 Gn, 5...300 Hz)<br>Shocks contactor open (6 Gn for 11 ms)<br>Shocks contactor closed (7 Gn for 11 ms) |
| Height                                                | 174 mm                                                                                                                                                                                 |

|            |          |
|------------|----------|
| Width      | 168.5 mm |
| Depth      | 181 mm   |
| Net Weight | 4.6 kg   |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type Of Package 1       | PCE       |
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 22 cm     |
| Package 1 Width              | 20 cm     |
| Package 1 Length             | 25 cm     |
| Package 1 Weight             | 5.1 kg    |
| Unit Type Of Package 2       | P06       |
| Number Of Units In Package 2 | 8         |
| Package 2 Height             | 77 cm     |
| Package 2 Width              | 80 cm     |
| Package 2 Length             | 60 cm     |
| Package 2 Weight             | 55.004 kg |
| Unit Type Of Package 3       | S06       |
| Number Of Units In Package 3 | 12        |
| Package 3 Height             | 73.5 cm   |
| Package 3 Width              | 60 cm     |
| Package 3 Length             | 80 cm     |
| Package 3 Weight             | 74.2 kg   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

 Mercury Free

 RoHS Exemption Information   [Yes](#)

## Certifications & Standards

|                          |                                                                                                                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                           |
| Eu Rohs Directive        | Compliant with Exemptions                                                                                                   |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                               |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | <a href="#">End of Life Information</a>                                                                                     |