

Product datasheet

Specifications



EasyPact TVS contactor 3P(3 NO) - AC-3 - <= 440 V 500A - 110 V AC coil

LC1E500F7

Price: 14,273.65 ZAR

Main

Range	Easy TeSys
Range Of Product	Easy TeSys Control
Product Or Component Type	Contactor
Device Short Name	LC1E
Contactor Application	Resistive load Motor control
Utilisation Category	AC-3 AC-1
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 50/60 Hz
[Ie] Rated Operational Current	500 A (at <55 °C) at <= 440 V AC AC-3 for power circuit 700 A (at <55 °C) at <= 440 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	110 V AC 50/60 Hz

Complementary

Motor Power Kw	147 kW at 220...230 V AC 50/60 Hz 250 kW at 380...400 V 280 kW at 415 V 295 kW at 440 V 335 kW at 500 V 355 kW at 660...690 V
Pole Contact Composition	3 NO
[Ith] Conventional Free Air Thermal Current	700 A (at 40 °C) for power circuit
Irms Rated Making Capacity	5000 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated Breaking Capacity	4000 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	4200 A 40 °C - 10 s for power circuit
Associated Fuse Rating	10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1 800 A gG at <= 690 V coordination type 1 for power circuit
Average Impedance	0.18 mOhm - Ith 700 A 50 Hz for power circuit
Power Dissipation Per Pole	45 W AC-3 88 W AC-1
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV coil not connected to the power circuit conforming to IEC 60947

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mechanical Durability	4000000 cycles
Electrical Durability	250000 cycles AC-1 600000 cycles AC-3
Control Circuit Type	AC at 50/60 Hz
Control Circuit Voltage Limits	0.85...1.1 Uc (-5...55 °C):operational 50/60 Hz 0.35...0.5 Uc (-5...55 °C):drop-out 50/60 Hz
Inrush Power In Va	1100 VA 50 Hz cos phi 0.9 (at 20 °C) 1100 VA 60 Hz cos phi 0.9 (at 20 °C)
Hold-In Power Consumption In Va	18 VA 50 Hz cos phi 0.9 (at 20 °C) 18 VA 60 Hz cos phi 0.9 (at 20 °C)
Heat Dissipation	18 W for control circuit 18 W
Operating Time	100...170 ms on opening 40...75 ms on closing
Maximum Operating Rate	2400 cyc/h 55 °C
Connections - Terminals	Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: solid without cable end Power circuit: cable with lug 2 - external diameter: 240 mm Power circuit: bars 2 - busbar cross section: 40 x 5 mm
Tightening Torque	Control circuit: 1.2 N.m Power circuit: 35 N.m
Minimum Switching Voltage	17 V for control circuit
Minimum Switching Current	5 mA for control circuit
Insulation Resistance	> 10 MOhm for control circuit
Non-Overlap Time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
Mounting Support	Plate

Environment

Standards	IEC 60947-5-1 IEC 60947-1 IEC 60947-4-1
Product Certifications	EAC CE
Ip Degree Of Protection	IP00 conforming to IEC 60529
Permissible Ambient Air Temperature Around The Device	-20...70 °C at Uc -60...80 °C storage -5...55 °C operation
Operating Altitude	3000 m without derating
Fire Resistance	850 °C conforming to IEC 60695-2-1
Mechanical Robustness	Shocks contactor closed (15 Gn for 11 ms) Vibrations contactor open (2 Gn, 5...300 Hz) Vibrations contactor closed (4 Gn, 5...300 Hz) Shocks contactor open (9 Gn for 11 ms)
Height	400 mm

Width	233 mm
Depth	232 mm
Net Weight	11.35 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	28.5 cm
Package 1 Length	28.5 cm
Package 1 Weight	11.35 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free	
 RoHS Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information