

Product datasheet

Specifications



High power contactor. TeSys Giga. 4 pole (4NO). AC-1 <=440V 385A. standard version. 100...250V wide band AC/DC coil

LC1G2654KUEH

Price: 33,309.31 ZAR

Main

Range	TeSys
Range Of Product	TeSys Giga
Product Or Component Type	Contactor
Device Short Name	LC1G
Contactor Application	Power switching
Utilisation Category	AC-3 AC-3e AC-1 AC-5a AC-5b AC-6a AC-6b DC-1 DC-3 DC-5
Poles Description	4P
[Ue] Rated Operational Voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] Rated Operational Current	265 A (at <60 °C) at <= 440 V AC-3 385 A (at <40 °C) at <= 1000 V AC-1
[Uc] Control Circuit Voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control Circuit Voltage Limits	Operational: 0.8 Uc Min...1.1 Uc Max (at <60 °C) Drop-out: 0.1 Uc Max...0.45 Uc Min (at <60 °C)

Complementary

[Uimp] Rated Impulse Withstand Voltage	8 kV
Overvoltage Category	III
[Ith] Conventional Free Air Thermal Current	385 A (at 40 °C)
Rated Breaking Capacity	2380 A at 440 V
[Icw] Rated Short-Time Withstand Current	2.2 kA - 10 s 1.23 kA - 30 s 0.95 kA - 1 min 0.62 kA - 3 min 0.48 kA - 10 min
Associated Fuse Rating	315 A aM at <= 440 V for motor 250 A aM at <= 690 V for motor 400 A gG at <= 690 V
Average Impedance	0.000144 Ohm
[Ui] Rated Insulation Voltage	1000 V

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Power Dissipation Per Pole	20 W AC-1 - lth 385 A 11 W AC-3 - lth 265 A
Compatibility Code	LC1G
Pole Contact Composition	4 NO
Auxiliary Contact Composition	1 NO + 1 NC
Irms Rated Making Capacity	3320 A at 440 V
Coil Technology	Built-in bidirectional peak limiting
Mechanical Durability	8 Mcycles
Inrush Power In Va (50/60 Hz, Ac)	700 VA
Inrush Power In W (Dc)	645 W
Hold-In Power Consumption In Va (50/60 Hz, Ac)	15.0 VA
Hold-In Power Consumption In W (Dc)	9.1 W
Operating Time	40...70 ms closing 15...50 ms opening
Maximum Operating Rate	600 cyc/h AC-3 600 cyc/h AC-3e 300 cyc/h AC-1
Connections - Terminals	Power circuit: bar 2 - busbar cross section: 32 x 10 mm Power circuit: lugs-ring terminals 1 185 mm ² Control circuit: push-in 1 0.2...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5...1.0 mm ² with cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: flexible with cable end
Connection Pitch	45 mm
Mounting Support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product Certifications	CB Scheme CCC cULus EAC CE UKCA EU-RO-MR by DNV-GL
Tightening Torque	35 N.m
Height	225 mm
Width	185 mm
Depth	226 mm
Net Weight	8.2 kg

Environment

Ip Degree Of Protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient Air Temperature For Operation	-25...60 °C
Ambient Air Temperature For Storage	-60...80 °C

Mechanical Robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective Treatment	TH
Permissible Ambient Air Temperature Around The Device	-40...70 °C at Uc

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	31.0 cm
Package 1 Length	32.0 cm
Package 1 Weight	9.072 kg
Unit Type Of Package 2	S06
Number Of Units In Package 2	4
Package 2 Height	45 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	46.288 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	
✓	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Installation

Installation Videos

- [TeSys Giga - How to install the auxiliary contact block](#)
- [TeSys Giga - How to install and remove remote wear diagnosis module](#)
- [TeSys Giga - How to install mechanical interlock kit](#)
- [TeSys Giga - How to install cable memory kit](#)
- [TeSys Giga - How to replace control module](#)
- [TeSys Giga - How to replace switching modules](#)
- [TeSys Giga - How to assemble change-over solution](#)