

# Product datasheet

Specifications



## TeSys LE - enclosed DOL starter - 1.8...2.6 A - 380 V AC coil

LE1M35Q708

**Price: 1,167.68 ZAR**

### Main

Range	TeSys
Product Name	TeSys LE
Device Short Name	LE1M
Product Or Component Type	Enclosed DOL starter
Device Application	Standard
Utilisation Category	AC-3
Device Composition	Contactor Earth terminal Neutral terminal Thermal overload relay
Thermal Protection Adjustment Range	1.8...2.6 A
Motor Power Kw	0.37 kW at 240 V AC 50/60 Hz 0.75 kW at 415 V AC 50/60 Hz 0.37 kW at 220/230 V AC 50/60 Hz 1.1 kW at 380/400 V AC 50/60 Hz
[Uc] Control Circuit Voltage	380 V AC 50/60 Hz
Control Type	Push-button start green I Push-button stop/reset red O

### Complementary

Local Signalling	Operating: LED (yellow)
Cable Entry Number	2 ISO20 top 2 ISO25 top 2 Pg 13 top 2 Pg 21 top 2 ISO20 bottom 2 ISO25 bottom 2 Pg 13 bottom 2 Pg 21 bottom 2 Pg 16 top 2 Pg 16 bottom
Width	78 mm
Height	160 mm
Depth	108 mm
Net Weight	0.6 kg

### Environment

Material	ABS (acrylonitrile butadiene-styrene)
Ip Degree Of Protection	IP65 conforming to IEC 60529

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Standards</b>	IEC 60947-4-1
<b>Ambient Air Temperature For Operation</b>	-5...40 °C
<b>Environmental Characteristic</b>	Standard environment
<b>Product Certifications</b>	UKCA

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	11.500 cm
<b>Package 1 Width</b>	8.000 cm
<b>Package 1 Length</b>	16.500 cm
<b>Package 1 Weight</b>	578.000 g
<b>Unit Type Of Package 2</b>	S02
<b>Number Of Units In Package 2</b>	6
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	3.775 kg
<b>Unit Type Of Package 3</b>	P06
<b>Number Of Units In Package 3</b>	96
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	71.460 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

---

Toxic Heavy Metal Free

---

Mercury Free

---

Rohs Exemption Information Yes

---

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant  
[EU RoHS Declaration](#)

---

**China Rohs Regulation** [China RoHS declaration](#)

---

**Environmental Disclosure** [Product Environmental Profile](#)

---

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

**Circularity Profile** [End of Life Information](#)

---