

Product datasheet

Specifications



PTC probe relay TeSys - LT3 with manual reset - 400V - 1 NO + 1 NC

LT3SM00V

Discontinued on: 09 Oct 2023

Price: 10,478.54 ZAR

Discontinued

Main

Range Of Product	LT3
Device Short Name	LT3SM
Product Or Component Type	Thermistor protection units
[Uc] Control Circuit Voltage	400 V AC 50/60 Hz
Reset	Manual

Complementary

Control Circuit Voltage Limits	0.85...1.1 Uc
Contacts Type And Composition	1 NC + 1 NO single voltage
[Ith] Conventional Free Air Thermal Current	5 A for output control relay
[Ui] Rated Insulation Voltage	Output control relay: 500 V AC
[Ue] Rated Operational Voltage	400 V AC 50/60 Hz for output control relay
Signalling Function	Fault indication Voltage indication
Control Type	Manual reset Manual test
Probe Interchangeability	Label mark A conforming to IEC 60034-11
Hold-In Power Consumption In W	1 W
Hold-In Power Consumption In Va	2.7 VA
Resistance	1500...1650 Ohm reset 2700...3100 Ohm tripping
Number Of Probes	0...6
Input Voltage	< 2.5 V (1500 Ohm) for probe < 7.5 V (4000 Ohm) for probe conforming to IEC 60034-11
Maximum Short Circuit Detection Resistance	20 Ohm
Condition Of Use	Connection of probes 1000 m >2.5 mm² Connection of probes 500 m >1.5 mm²
[Uimp] Rated Impulse Withstand Voltage	2.5 kV
Rated Power In Va	100 VA at 220 V - electrical durability: 500000 cycles
Breaking Capacity	2 A at 24 V DC DC-13 3 A at 250 V AC AC-16 6 A at 120 V AC AC-16

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - Terminals	Power circuit: cage type connector 1 cable(s) 0.75...2.5 mm²flexible with cable end Power circuit: cage type connector 1 cable(s) 0.75...2.5 mm²solid with cable end Power circuit: cage type connector 1 cable(s) 1...2.5 mm²flexible without cable end Power circuit: cage type connector 1 cable(s) 1...2.5 mm²solid without cable end Power circuit: cage type connector 2 cable(s) 0.75...2.5 mm²flexible with cable end Power circuit: cage type connector 2 cable(s) 0.75...2.5 mm²solid with cable end Power circuit: cage type connector 2 cable(s) 1...2.5 mm²flexible without cable end Power circuit: cage type connector 2 cable(s) 1...2.5 mm²solid without cable end
Tightening Torque	0.8 N.m
Height	100 mm
Width	22.5 mm
Depth	100 mm
Net Weight	0.22 kg

Environment

Standards	IEC 60947-8 IEC 60034-11 VDE 0660
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP20 conforming to VDE 0106
Ambient Air Temperature For Operation	-25...60 °C
Ambient Air Temperature For Storage	-40...85 °C conforming to IEC 60068-2-2 -40...85 °C conforming to IEC 60068-2-2
Operating Altitude	<= 1500 m without derating in temperature > 1500...3000 m with derating in temperature
Vibration Resistance	1 gn 25...150 Hz conforming to IEC 60068-2-6 2.5 gn 2...25 Hz conforming to IEC 60068-2-6
Shock Resistance	5 gn 11 ms conforming to IEC 60068-2-27
Electromagnetic Compatibility	Resistance to electrostatic discharge level 3 conforming to IEC 61000-4-2 Resistance to fast transient level 3 conforming to IEC 61000-4-4 Surge resistance 1.2/50-8/20 level 4 conforming to IEC 61000-4-5 Susceptibility to electromagnetic fields level 3 conforming to IEC 61000-4-3 Immunity to microbreaks and voltage drops conforming to IEC 61000-4-11

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	10.3 cm
Package 1 Length	10.3 cm
Package 1 Weight	197.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	36
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.547 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins