

Product datasheet

Specifications



Earth-leakage VigipacT add-on protection module. ComPacT NSX 100/160. 200 VAC to 440 VAC. 30 mA to 30 A. 3 poles

LV429488

Price: 10,255.45 ZAR

Main

Range Of Product	ComPacT NSX100...250 new generation ComPacT NSX100...250
Device Short Name	VigiPacT
Product Or Component Type	Vigi add-on
Device Application	Wiring
Range Compatibility	ComPacT new generation ComPacT NSX100 new generation circuit breaker ComPacT new generation ComPacT NSX160 new generation circuit breaker ComPacT ComPacT NSX100 circuit breaker ComPacT ComPacT NSX160 circuit breaker
Poles Description	3P
[In] Rated Current	100 A 160 A
Earth-Leakage Protection Class	Class A Class AC
Residual Earth-Leakage Sensitivity Adjustment Type	Adjustable
Earth-Leakage Sensitivity	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC
Residual Earth-Leakage Time Delay Adjustment Type	Adjustable
[Δt] Residual Earth-Leakage Time Delay Adjustment	0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s 4 s

Complementary

Network Type	AC
Network Frequency	50/60 Hz
[Ue] Rated Operational Voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-Leakage Protection	With
Maximum Breaking Time	800 ms
Overvoltage Category	IV

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Electrical Shock Protection Class	Class II
Standards	IEC 60947-2

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.000 cm
Package 1 Width	14.500 cm
Package 1 Length	17.000 cm
Package 1 Weight	1.093 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	12
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	13.735 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	48
Package 3 Height	42.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	67.200 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free

 RoHS Exemption Information Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information