

# Product datasheet

Specifications



Earth-leakage VigiPacT add-on protection module. ComPacT NSX 100/160. 200 VAC to 440 VAC. 30 mA to 30 A. 4 poles

LV429489

**Price: 8,339.42 ZAR**

## Main

<b>Range Of Product</b>	ComPacT NSX100...250 new generation ComPacT NSX100...250
<b>Device Short Name</b>	VigiPacT
<b>Product Or Component Type</b>	Vigi add-on
<b>Device Application</b>	Wiring
<b>Range Compatibility</b>	ComPacT new generation ComPacT NSX100 new generation circuit breaker ComPacT new generation ComPacT NSX160 new generation circuit breaker ComPacT ComPacT NSX100 circuit breaker ComPacT ComPacT NSX160 circuit breaker
<b>Poles Description</b>	4P
<b>[In] Rated Current</b>	100 A 160 A
<b>Earth-Leakage Protection Class</b>	Class A Class AC
<b>Residual Earth-Leakage Sensitivity Adjustment Type</b>	Adjustable
<b>Earth-Leakage Sensitivity</b>	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC
<b>Residual Earth-Leakage Time Delay Adjustment Type</b>	Adjustable
<b>[Δt] Residual Earth-Leakage Time Delay Adjustment</b>	0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s 4 s

## Complementary

<b>Network Type</b>	AC
<b>Network Frequency</b>	50/60 Hz
<b>[Ue] Rated Operational Voltage</b>	200...440 V AC 50/60 Hz conforming to IEC 60947-2
<b>Earth-Leakage Protection</b>	With
<b>Maximum Breaking Time</b>	800 ms
<b>Overvoltage Category</b>	IV

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

## Environment

---

Electrical Shock Protection Class	Class II
-----------------------------------	----------

---

Standards	IEC 60947-2
-----------	-------------

---

## Packing Units

---

Unit Type Of Package 1	PCE
------------------------	-----

---

Number Of Units In Package 1	1
------------------------------	---

---

Package 1 Height	13.400 cm
------------------	-----------

---

Package 1 Width	14.500 cm
-----------------	-----------

---

Package 1 Length	17.200 cm
------------------	-----------

---

Package 1 Weight	1.315 kg
------------------	----------

---

Unit Type Of Package 2	S04
------------------------	-----

---

Number Of Units In Package 2	12
------------------------------	----

---

Package 2 Height	30.000 cm
------------------	-----------

---

Package 2 Width	40.000 cm
-----------------	-----------

---

Package 2 Length	60.000 cm
------------------	-----------

---

Package 2 Weight	16.430 kg
------------------	-----------

---

Unit Type Of Package 3	P12
------------------------	-----

---

Number Of Units In Package 3	48
------------------------------	----

---

Package 3 Height	42.000 cm
------------------	-----------

---

Package 3 Width	80.000 cm
-----------------	-----------

---

Package 3 Length	120.000 cm
------------------	------------

---

Package 3 Weight	80.000 kg
------------------	-----------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)