

Product datasheet

Specifications



switch disconnecter ComPact NSX400 NA DC. 3 poles. 400 A

LV438153

Discontinued on: 20 Nov 2023

Discontinued

Main

Range	ComPact
Product Name	ComPact NSX DC
Product Or Component Type	Switch disconnecter
Device Short Name	Compact NSX400NA DC
Poles Description	3P
Network Type	DC
[Ue] Rated Operational Voltage	750 V DC conforming to IEC 60947-3
[Ie] Rated Operational Current	DC-22A: 400 A DC 750 V
[Ui] Rated Insulation Voltage	750 V DC conforming to IEC 60947-3
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947-3
[Ith] Conventional Free Air Thermal Current	400 A
[Icm] Rated Short-Circuit Making Capacity	7.5 kA switch-disconnector alone
Breaking Capacity Code	NA
Suitability For Isolation	Yes conforming to EN 60947-3
Contact Position Indicator	Yes
Visible Break	No
Utilisation Category	DC-22A
Pollution Degree	3 conforming to IEC 60947-3

Complementary

Control Type	Toggle
Mounting Mode	Fixed
Upside Connection	Front
Downside Connection	Front
[Icw] Rated Short-Time Withstand Current	7.5 kA during 1 s conforming to IEC 60947-3
Mechanical Durability	5000 cycles conforming to IEC 60947-3
Electrical Durability	1000 cycles 750 V DC In conforming to IEC 60947-3 2000 cycles 750 V DC In/2
Connection Pitch	45 mm
Height	255 mm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	140 mm
Depth	110 mm
Net Weight	6 kg

Environment

Standards	EN/IEC 60947-3
Product Certifications	CE
Ip Degree Of Protection	IP20 conforming to IEC 60529
Electrical Shock Protection Class	Class II

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14.7 cm
Package 1 Width	20.0 cm
Package 1 Length	29.1 cm
Package 1 Weight	5.35 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



RoHS/REACH

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins