

Product datasheet

Specifications



fuse switch disconnecter. FuPacT
ISFL400. 400A. 3 poles switchable.
connection to 185mm busbars. M12
screws

LV480857

Price: 8,600.90 ZAR

Main

Range	FuPacT
Product Name	FuPacT ISFL
Device Short Name	ISFL400
Product Or Component Type	Fuse-switch disconnecter
Device Application	Equipment protection, monitoring and control Distribution
Signalling Function	Separated fuse monitor
Poles Description	1 x 3P switchable
Number Of Fuse Carriers	3
Fuse Type	DIN
Fuse Size	NH2
Suitability For Isolation	Yes conforming to EN/IEC 60947-3
Visible Break	Yes
Contact Position Indicator	Yes
[Ith] Conventional Free Air Thermal Current	400 A (40 °C) power dissipation per fuse: 34 W
[Ithe] Conventional Enclosed Thermal Current	400 A at 40 °C, Power dissipation per fuse: 34 W
Maximum Power Dissipation Per Pole	53 W
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz 800 V AC 50/60 Hz AC-20 800 V DC DC-20
[Ui] Rated Insulation Voltage	1000 V AC 50/60 Hz 1000 V DC
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ie] Rated Operational Current	AC-21B: 400 A at 220/240 V AC 50/60 Hz AC-21B: 400 A at 380/415 V AC 50/60 Hz AC-21B: 400 A at 440/480 V AC 50/60 Hz AC-21B: 400 A at 500 V AC 50/60 Hz AC-21B: 400 A at 660/690 V AC 50/60 Hz AC-22B: 400 A at 220/240 V AC 50/60 Hz AC-22B: 400 A at 380/415 V AC 50/60 Hz AC-22B: 400 A at 440/480 V AC 50/60 Hz AC-22B: 400 A at 500 V AC 50/60 Hz AC-23B: 400 A at 220/240 V AC 50/60 Hz AC-23B: 400 A at 380/415 V AC 50/60 Hz

Complementary

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Iq] Breaking Capacity With Fuses (Ka Rms)	120 kA at 415 V (AC) 120 kA at 500 V (AC) 120 kA at 690 V (AC)
[Icw] Rated Short-Time Withstand Current	15 kA for 1 s
[Icm] Rated Short-Circuit Making Capacity	30 kA at 690 V
Rated Duty	Uninterrupted
Control Type	Fuse carriers handle
Provision For Padlocking	3 padlocks
Mounting Position	Vertical
Mounting Mode	Fixed
Mounting Support	Busbars
Mounting Location	One above the other
Contact Operation	Single-break
Mechanical Durability	800 cycles
Electrical Durability	AC-21B: 200 cycles 690 V AC 50/60 Hz AC-22B: 200 cycles 500 V AC 50/60 Hz AC-23B: 200 cycles 415 V AC 50/60 Hz
Connections - Terminals	Screw connection downstream M12 400 A Direct connection upstream 400 A 185 mm
Tightening Torque	40 N.m
Width	100 mm
Height	741 mm
Depth	190 mm
Net Weight	5 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product Certifications	CE CCC EAC

Environment

Electrical Shock Protection Class	Class II front face
Ip Degree Of Protection	IP20 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to EN 50102
Pollution Degree	3 conforming to IEC 60947
Ambient Air Temperature For Operation	-20...70 °C
Ambient Air Temperature For Storage	-50...85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	21.600 cm
Package 1 Length	79.000 cm

Package 1 Weight	5.533 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	50
Package 2 Height	122.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	288.500 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation		REACH Declaration
Eu Rohs Directive		Compliant EU RoHS Declaration
China Rohs Regulation		China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee		The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins