

# Product datasheet

Specifications



current transformer. FuPacT ISFL250 to ISFL1250. class 1. 400/5A. 5VA

LV480887

Price: 1,791.31 ZAR

## Main

|                           |                                                                                                                                                |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Range Of Product          | ISFL1250<br>ISFL250...630                                                                                                                      |
| Range                     | FuPacT                                                                                                                                         |
| Product Or Component Type | Current transformer                                                                                                                            |
| Device Application        | Power supply                                                                                                                                   |
| Range Compatibility       | FuPacT FuPacT ISFL ISFL250 fuse-switch disconnecter<br>FuPacT FuPacT ISFL ISFL400<br>FuPacT FuPacT ISFL ISFL630<br>FuPacT FuPacT ISFL ISFL1250 |
| Current Transformer Ratio | 400/5 A                                                                                                                                        |
| Power Consumption In Va   | 5 VA                                                                                                                                           |

## Complementary

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Accessory / Separate Part Categor     | Measurement accessory              |
| Current Transformer Type              | Measurement class 1                |
| Maximum Safety Factor                 | 5                                  |
| [Ue] Rated Operational Voltage        | 800 V AC 50/60 Hz                  |
| Ip Degree Of Protection               | IP20                               |
| Standards                             | IEC 60044-1<br>VDE 0414<br>BS 7626 |
| Ambient Air Temperature For Operation | -25...70 °C                        |
| Ambient Air Temperature For Storage   | -40...80 °C                        |
| Height                                | 78 mm                              |
| Width                                 | 60 mm                              |
| Depth                                 | 30 mm                              |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type Of Package 1       | PCE     |
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 4.6 cm  |
| Package 1 Width              | 6.5 cm  |
| Package 1 Length             | 8.0 cm  |
| Package 1 Weight             | 163.0 g |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 2       | S02      |
| Number Of Units In Package 2 | 40       |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 6.975 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

Well-being performance

|   |                            |     |
|---|----------------------------|-----|
| ✓ | Reach Free Of Svhc         |     |
| ✓ | Toxic Heavy Metal Free     |     |
| ✓ | Mercury Free               |     |
| ✓ | Rohs Exemption Information | Yes |

Certifications & Standards

|                          |                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                           |
| Eu Rohs Directive        | Compliant<br><a href="#">EU RoHS Declaration</a>                                                            |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                               |
| Circularity Profile      | No need of specific recycling operations                                                                    |