

Product datasheet

Specifications



Circuit breaker Masterpact MTZ1 10L1. 1000 A. 3P drawout. without Micrologic

LV847222

Price: 101,246.44 ZAR

Main

Range	MasterPacT
Product Name	MasterPact MTZ1
Device Short Name	MTZ1 10 L1
Product Or Component Type	Circuit breaker
Device Application	Power distribution protection
Poles Description	3P
Control Unit	Without control unit
Product Compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
[In] Rated Current	1000 A at 40 °C
Performance Type	L1 150 kA 415 V AC
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
Suitability For Isolation	Yes conforming to EN/IEC 60947-2
Selectivity Category	Category A
Control Type	Push-button
Mounting Mode	Drawout

Complementary

[Icu] Rated Ultimate Short-Circuit Breaking Capacity	150 kA at 220/415 V AC 50/60 Hz 130 kA at 440 V AC 50/60 Hz 100 kA at 500/525 V AC 50/60 Hz
[Ics] Rated Service Breaking Capacity	150 kA at 220/415 V AC 50/60 Hz 130 kA at 440 V AC 50/60 Hz 100 kA at 500/525 V AC 50/60 Hz
[Icw] Rated Short-Time Withstand Current	10 kA 0.5 s
[Icm] Rated Short-Circuit Making Capacity	330 kA 220/415 V AC at 50/60 Hz 286 kA 440 V AC at 50/60 Hz 220 kA 500/525 V AC at 50/60 Hz 52 kA 660/690 V AC at 50/60 Hz
Integrated Instantaneous Protection (Din In Ka Peak)	9...11 kA

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Sensor Rating	400 A 630 A 800 A 1000 A
[U_i] Rated Insulation Voltage	1000 V AC 50/60 Hz
[U_{imp}] Rated Impulse Withstand Voltage	12 kV
Power Dissipation In W	230 W
Maximum Breaking Time	9 ms
Maximum Closing Response Time	50 ms
Mounting Support	Rails Base plate
Upside Connection	Front Rear
Downside Connection	Front Rear
Connection Pitch	70 mm
Mechanical Durability	12500 cycles with periodic preventive maintenance
Electrical Durability	AC-23A: 3000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 2000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 3000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2
Height	Drawout circuit breaker with chassis: 322 mm Drawout circuit breaker without chassis: 259.5 mm
Width	Drawout circuit breaker with chassis: 288 mm Drawout circuit breaker without chassis: 236.5 mm
Depth	Drawout circuit breaker with chassis: 291 mm Drawout circuit breaker without chassis: 207.5 mm
Net Weight	30 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product Certifications	CE IECEE CB Scheme

Environment

Ip Degree Of Protection	IP30 conforming to EN 60529
Pollution Degree	3 conforming to IEC 60947-1
Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-40...85 °C
Operating Altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	36.0 cm
Package 1 Width	40.0 cm
Package 1 Length	23.0 cm

Package 1 Weight

16.224 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Pvc Free

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)