


Product datasheet

Specifications



2nd MX opening voltage release.
standard. Masterpact MTZ1
drawout. 100/130 VAC 50/60 Hz.
100/130 VDC

LV847452

Price: 5,350.22 ZAR

Main

Range	MasterPact
Device Short Name	second MX
Product Or Component Type	Voltage release
Device Application	Control
Range Compatibility	Masterpact MasterPact MTZ1 circuit-breaker
Voltage Release Type	Shunt trip release

Complementary

Control Type	Standard
[Un] Voltage Power Supply	100...130 V AC 50/60 Hz 100...130 V DC
Threshold Tripping Voltage	0.7...1.1 Un on opening
Holding Power Consumption	4.5 W
Circuit Breaker Mounting Mode	Drawout
Maximum Response Time	60 ms on opening for MasterPact MTZ1

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.3 cm
Package 1 Length	8.1 cm
Package 1 Weight	1.167 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free

 RoHS Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information