

Product datasheet

Specifications



TeSys D - contactor coil - LX4D8 - 24 V DC standard for 115 & 150 A contactor

LX4D8BD

Price: 4,108.05 ZAR

Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX4D8
Control Circuit Type	DC standard
[Uc] Control Circuit Voltage	24 V DC
Average Resistance	147 Ohm at 20 °C
Inductance Of Closed Circuit	3.03 H
Product Compatibility	LC1D150 LC1D115
Mechanical Durability	8 Mcycles
Maximum Operating Rate	1200 cyc/h 60 °C

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational: 0.75...1.2 Uc (at <55 °C) Drop-out: 0.15...0.4 Uc (at <55 °C)
Time Constant	25 ms
Inrush Power In W	270...365 W (at 20 °C)
Hold-In Power Consumption In W	2.4...5.1 W at 20 °C

Environment

Ambient Air Temperature For Operation	-5...60 °C
Net Weight	0.3 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.2 cm
Package 1 Width	11.4 cm
Package 1 Length	17.2 cm
Package 1 Weight	293.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	20

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.347 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

	Reach Free Of Svhc	
	Mercury Free	
	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations