


Product datasheet

Specifications



TeSys F - contactor coil - LX4FF - 24 V DC

LX4FF024

⚠ To be discontinued on: 31 Dec 2028

⚠ To be discontinued

Price: 6,630.39 ZAR

Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX4FF
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F150 LC1F115
Control Circuit Type	DC low consumption
[Uc] Control Circuit Voltage	24 V DC
Inductance Of Closed Circuit	11 H
Average Resistance	1.12 Ohm inrush at 20 °C 177 Ohm holding at 20 °C
Operating Time	30...40 ms closing 30...50 ms opening
Mechanical Durability	10 Mcycles
Maximum Operating Rate	2400 cyc/h 55 °C

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational: 0.85...1.1 Uc (at 55 °C) Drop-out: 0.15...0.2 Uc (at 55 °C)
Inrush Power In W	560 W (at 20 °C)
Hold-In Power Consumption In W	4.5 W at 20 °C

Environment

Ambient Air Temperature For Operation	-5...55 °C
Net Weight	0.43 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.300 cm
Package 1 Width	8.200 cm
Package 1 Length	15.800 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Package 1 Weight	528.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	14
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.824 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
