

# Product datasheet

Specifications



## Multi 9 - C60BP - MCB - 2P - 2 A - D Curve - 480Y/277 V - 10 kA - UL 489

M9F43202

**Price: 712.43 ZAR**

### Main

Range	Multi9
Product Name	Multi9 C60
Product Or Component Type	Miniature circuit-breaker
Device Short Name	C60BP
Device Application	Distribution
Poles Description	2P
Number Of Protected Poles	2
[In] Rated Current	2 A at 25 °C conforming to EN/IEC 60947-2
Network Type	DC AC
Trip Unit Technology	Thermal-magnetic
Curve Code	D
Breaking Capacity	6 kA Icu at 440 V AC conforming to EN/IEC 60947-2 10 kA Icu at 415 V AC conforming to EN/IEC 60947-2 20 kA Icu at 240 V AC conforming to EN/IEC 60947-2 6 kA Icu at 440 V AC conforming to GB 14048.2 10 kA Icu at 415 V AC conforming to GB 14048.2 20 kA Icu at 240 V AC conforming to GB 14048.2 14 kA AIR at 240 V AC conforming to UL 489 10 kA AIR at 125 V DC conforming to UL 489 10 kA AIR at 480Y/277 V AC conforming to UL 489 14 kA AIR at 240 V AC conforming to CSA C22.2 No 5 10 kA AIR at 480Y/277 V AC conforming to CSA C22.2 No 5 10 kA AIR at 125 V DC conforming to CSA C22.2 No 5
Suitability For Isolation	Yes conforming to EN/IEC 60947-2
Standards	EN/IEC 60947-2 GB 14048.2 UL 489 CSA C22.2 No 5
Product Certifications	IEC CCC CSA UL

### Complementary

[Ue] Rated Operational Voltage	240 V AC 50/60 Hz 415 V AC 50/60 Hz 440 V AC 50/60 Hz
Magnetic Tripping Limit	12 x In +/- 20 % AC 17 x In +/- 20 % DC

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>[Ics] Rated Service Breaking Capacity</b>	4.5 kA 75 % conforming to EN/IEC 60947-2 - 440 V AC 7.5 kA 75 % conforming to EN/IEC 60947-2 - 415 V AC 15 kA 75 % conforming to EN/IEC 60947-2 - 240 V AC 4.5 kA 75 % conforming to GB 14048.2 - 440 V AC 7.5 kA 75 % conforming to GB 14048.2 - 415 V AC 15 kA 75 % conforming to GB 14048.2 - 240 V AC
<b>[Ui] Rated Insulation Voltage</b>	500 V AC conforming to EN/IEC 60947-2
<b>[Uimp] Rated Impulse Withstand Voltage</b>	6 kV conforming to EN/IEC 60947-2
<b>Contact Position Indicator</b>	Yes
<b>Control Type</b>	Toggle
<b>Local Signalling</b>	ON/OFF indication
<b>Mounting Mode</b>	Clip-on
<b>Mounting Support</b>	DIN rail
<b>9 Mm Pitches</b>	4
<b>Height</b>	103 mm
<b>Width</b>	36 mm
<b>Depth</b>	72 mm
<b>Colour</b>	Grey
<b>Mechanical Durability</b>	20000 cycles
<b>Electrical Durability</b>	10000 cycles
<b>Provision For Padlocking</b>	Padlockable
<b>Connections - Terminals</b>	Tunnel type terminal (top or bottom)1...25 mm <sup>2</sup> (AWG 18...AWG 8) - rigid Tunnel type terminal (top or bottom)1...16 mm <sup>2</sup> (AWG 18...AWG 8) - flexible with ferrule Tunnel type terminal (top or bottom)1...16 mm <sup>2</sup> (AWG 18...AWG 8) - flexible
<b>Wire Stripping Length</b>	14 mm for top or bottom connection
<b>Tightening Torque</b>	2.5 N.m top or bottom
<b>Earth-Leakage Protection</b>	Without

## Environment

<b>Ip Degree Of Protection</b>	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
<b>Pollution Degree</b>	3 conforming to EN/IEC 60947-2
<b>Tropicalisation</b>	2 conforming to IEC 60068-1
<b>Relative Humidity</b>	95 % at 55 °C
<b>Operating Altitude</b>	0...2000 m
<b>Ambient Air Temperature For Operation</b>	-30...70 °C
<b>Ambient Air Temperature For Storage</b>	-40...80 °C

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	3.6 cm
<b>Package 1 Width</b>	7.5 cm
<b>Package 1 Length</b>	10.3 cm

<b>Package 1 Weight</b>	247 g
<b>Unit Type Of Package 2</b>	BB1
<b>Number Of Units In Package 2</b>	6
<b>Package 2 Height</b>	8.3 cm
<b>Package 2 Width</b>	10.8 cm
<b>Package 2 Length</b>	22 cm
<b>Package 2 Weight</b>	1.54 kg
<b>Unit Type Of Package 3</b>	S03
<b>Number Of Units In Package 3</b>	54
<b>Package 3 Height</b>	30 cm
<b>Package 3 Width</b>	30 cm
<b>Package 3 Length</b>	40 cm
<b>Package 3 Weight</b>	14.316 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations