

# Product datasheet

Specifications



EasyLogic PM2120. Power & Energy meter. up to the 15th harmonic. LED display. RS485. class 1

METSEPM2120

**Price: 6,670.71 ZAR**

## Main

Range	EasyLogic
Product Name	EasyLogic PM2100
Device Short Name	PM2120
Product Or Component Type	Power meter

## Complementary

Device Application	Sub billing Power monitoring
Power Quality Analysis	total harmonic distortion up to the 15th harmonic
Type Of Measurement	Apparent power min/max, total Active and reactive power min/max, total Current min/max, avg Voltage min/max, avg Frequency min/max, avg Total current harmonic distortion THD (I) per phase Total voltage harmonic distortion THD (U) per phase Power factor min/max, avg Apparent energy total Active and reactive energy total
Metering Type	Current I, I1, I2, I3 Peak demand power PM, QM, SM Active, reactive, apparent energy (signed, four quadrant) Peak demand currents Active power P, P1, P2, P3 Calculated neutral current Voltage U, U21, U32, U13, V, V1, V2, V3 Unbalance current Reactive power Q, Q1, Q2, Q3 Demand power P, Q, S Apparent power S, S1, S2, S3
Accuracy Class	Class 1 active energy conforming to IEC 62053-21 Class 1 reactive energy conforming to IEC 62053-24 Class 5 harmonic distortion (I THD & U THD)
Measurement Accuracy	Apparent power +/- 1 % Active energy +/- 1 % Reactive energy +/- 1 % Active power +/- 1 % Voltage +/- 0.5 % Power factor +/- 0.01 Current +/- 0.5 % Frequency +/- 0.05 %
Measurement Current	5...6000 mA
Measurement Voltage	35...480 V AC 50/60 Hz between phases 20...277 V AC 50/60 Hz between phase and neutral 480...999000 V AC 50/60 Hz with external VT

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Frequency Measurement Range</b>	45...65 Hz
<b>[Us] Rated Supply Voltage</b>	44...277 V AC 45...65 Hz +/- 10 % 44...277 V DC +/- 10 %
<b>Network Frequency</b>	50 Hz 60 Hz
<b>Ride-Through Time</b>	100 ms 120 V AC typical 400 ms 230 V AC typical 50 ms 125 V DC typical
<b>[In] Rated Current</b>	1 A 5 A
<b>Maximum Power Consumption In Va</b>	6 VA at 277 V AC
<b>Maximum Power Consumption In W</b>	3.3 W (power lines (AC)) 2 W at 277 V (power lines (DC))
<b>Input Impedance</b>	Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)
<b>Tamperproof Of Settings</b>	Protected by access code
<b>Display Type</b>	7 segments LED
<b>Display Colour</b>	Red
<b>Messages Display Capacity</b>	3 fields of 4 characters
<b>Display Digits</b>	12 digit(s) - 14.2 mm in height
<b>Demand Intervals</b>	Configurable from 1 to 60 min
<b>Information Displayed</b>	Demand current (past value) Demand current (present value) Demand power (past value) Demand power (present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in %
<b>Control Type</b>	3 x button
<b>Local Signalling</b>	Red LED: output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED: module operation and integrated communication
<b>Number Of Inputs</b>	0
<b>Number Of Outputs</b>	0
<b>Communication Port Protocol</b>	Modbus RTU at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires, insulation 2500 V
<b>Communication Port Support</b>	Screw terminal block: RS485
<b>Data Recording</b>	Time stamping Min/max for 8 parameters
<b>Function Available</b>	Real time clock
<b>Sampling Rate</b>	64 samples/cycle
<b>Cybersecurity</b>	Enable/disable communication ports
<b>Communication Service</b>	Remote monitoring

<b>Product Certifications</b>	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 RCM EAC C-Tick
<b>Mounting Mode</b>	Clip-on
<b>Mounting Position</b>	Vertical
<b>Mounting Support</b>	Framework
<b>Provided Equipment</b>	1 x installation guide
<b>Measurement Category</b>	Category III 480 V Category II 480...600 V
<b>Electrical Insulation Class</b>	Double insulation Class II
<b>Flame Retardance</b>	V-0 conforming to UL 94
<b>Connections - Terminals</b>	Current transformer: screw connection (bottom) 6 Voltage inputs: screw connection (top) 4
<b>Material</b>	Polycarbonate
<b>Width</b>	96 mm
<b>Depth</b>	Total : 76.09 mm Embedded : 61.64 mm
<b>Height</b>	96 mm
<b>Net Weight</b>	300 g
<b>Compatibility Code</b>	PM2120

## Environment

<b>Service Life</b>	7 year(s)
<b>Ip Degree Of Protection</b>	IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
<b>Relative Humidity</b>	5...95 % at 50 °C
<b>Pollution Degree</b>	2
<b>Ambient Air Temperature For Operation</b>	-10...60 °C
<b>Ambient Air Temperature For Storage</b>	-25...70 °C
<b>Operating Altitude</b>	<= 2000 m
<b>Electromagnetic Compatibility</b>	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A
<b>Overvoltage Category</b>	III

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	9.6 cm
<b>Package 1 Width</b>	6.72 cm

---

<b>Package 1 Length</b>	10.16 cm
-------------------------	----------

---

<b>Package 1 Weight</b>	302.5 g
-------------------------	---------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)