

# Product datasheet

Specifications



## EasyLogic PM2X30 - I/O Module - Analogue - 2 inputs + 2 outputs

METSEPM2KANLGIO22

Price: 2,295.25 ZAR

### Main

Range	EasyLogic
Device Short Name	PM2K2AIAO
Product Or Component Type	I/O module
Device Application	Optional expansion module
Range Compatibility	EasyLogic EasyLogic PM2100 PM2130 EasyLogic EasyLogic PM2200 PM2230

### Complementary

[Ui] Rated Insulation Voltage	2500 V
Number Of Outputs	2 analog, 4...20 mA
Output Voltage	12 V AC
Analogue Input Type	Analog input (impedance <= 300 Ohm)
Number Of Inputs	2 analog 4...20 mA
Input Voltage	12...30 V AC
Analogue Output Type	Analog output, impedance <600 Ohm
Width	90.5 mm
Depth	14.6 mm
Height	53 mm
Net Weight	50 g

### Environment

Ambient Air Temperature For Operation	-10...60 °C
Ambient Air Temperature For Storage	-25...70 °C

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.38 cm
Package 1 Width	9.91 cm
Package 1 Length	5.08 cm
Package 1 Weight	0.11 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)