

# Product datasheet

Specifications



Socket-outlet. Mureva Styl. 2P + E  
with shutters. pin earth. 16A.  
250V. flush. white

MUR39133

Price: 127.48 ZAR

## Main

|                             |                  |
|-----------------------------|------------------|
| Range                       | Mureva Styl      |
| Range Of Product            | Mureva Styl      |
| Product Or Component Type   | Socket-outlet    |
| Device Presentation         | Complete product |
| Outlet Poles Configuration  | 2P + E           |
| Outlet Standard Description | Pin earth        |
| Outlet Standard             | French           |
| Colour Tint                 | White (RAL 9003) |

## Complementary

|                                            |                                                                                                                                                                                                                                                                                                                                     |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device Mounting                            | Flush<br>Surface                                                                                                                                                                                                                                                                                                                    |
| Cover Type                                 | With shutter                                                                                                                                                                                                                                                                                                                        |
| Socket Number                              | 1                                                                                                                                                                                                                                                                                                                                   |
| Rated Current                              | 16 A                                                                                                                                                                                                                                                                                                                                |
| [Ue] Rated Operational Voltage             | 250 V AC                                                                                                                                                                                                                                                                                                                            |
| Condition Of Use                           | Indoor/outdoor                                                                                                                                                                                                                                                                                                                      |
| Material                                   | PC (polycarbonate)<br>PP (polypropylene)<br>Brass                                                                                                                                                                                                                                                                                   |
| Fixing Mode                                | By screws                                                                                                                                                                                                                                                                                                                           |
| Clamping Connection Capacity               | 1...2.5 mm <sup>2</sup> for rigid cable(s)<br>1...2.5 mm <sup>2</sup> for stranded cable(s)<br>1...2.5 mm <sup>2</sup> for flexible cable(s)                                                                                                                                                                                        |
| Wire Stripping Length                      | 13 mm                                                                                                                                                                                                                                                                                                                               |
| Height                                     | 71 mm                                                                                                                                                                                                                                                                                                                               |
| Width                                      | 71 mm                                                                                                                                                                                                                                                                                                                               |
| Depth                                      | 47 mm                                                                                                                                                                                                                                                                                                                               |
| Chemical And Detergent Products Resistance | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Environment

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| Quality Labels                        | NF                                                    |
| Ip Degree Of Protection               | IP55                                                  |
| Ik Degree Of Protection               | IK08                                                  |
| Flame Retardance                      | Self-extinguishing 650 °C conforming to IEC 60695-2-1 |
| Ambient Air Temperature For Operation | -5...40 °C                                            |
| Ambient Air Temperature For Storage   | -25...55 °C                                           |

# Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type Of Package 1       | PCE       |
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 7.100 cm  |
| Package 1 Width              | 4.000 cm  |
| Package 1 Length             | 7.100 cm  |
| Package 1 Weight             | 63.000 g  |
| Unit Type Of Package 2       | BB1       |
| Number Of Units In Package 2 | 10        |
| Package 2 Height             | 8.000 cm  |
| Package 2 Width              | 15.900 cm |
| Package 2 Length             | 39.500 cm |
| Package 2 Weight             | 721.000 g |
| Unit Type Of Package 3       | S04       |
| Number Of Units In Package 3 | 60        |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 40.000 cm |
| Package 3 Length             | 60.000 cm |
| Package 3 Weight             | 5.060 kg  |

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Sustainable Packaging   Transparency   RoHS/REACH

Resource performance

 Sustainable Packaging

Well-being performance

 Mercury Free

 Rohs Exemption Information   [Yes](#)

Certifications & Standards

|                          |                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                     |
| Eu Rohs Directive        | Compliant with Exemptions                                                                                             |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                         |
| Circularity Profile      | No need of specific recycling operations                                                                              |