

Product datasheet

Specifications



ClimaSys forced vent. IP54. 38m3/h. 115V. with outlet grille and filter G2

NSYCVF38M115PF

Price: 1,580.21 ZAR

Main

Range	ClimaSys
Product Name	ClimaSys CV
Product Or Component Type	Fan
Type Of Filter	Standard
Flow Rate	Free flow rate with standard filter: 38 m3/h at 50 Hz Free flow rate with standard filter: 39 m3/h at 60 Hz
[Us] Rated Supply Voltage	75...125 V
Input Voltage	115 V 50/60 Hz

Complementary

Absorbed Power	3.3 W 50 Hz 3.5 W 60 Hz
[In] Rated Current	0.16 A 50 Hz 0.16 A 60 Hz
Noise Level < At	40...41 dB
Bearing Type	Ball
Height	External: 137 mm
Width	External: 117 mm
Depth	External : 49 mm
Cut-Out Dimensions	92 x 92 mm
Net Weight	0.22 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient Air Temperature For Operation	-10...70 °C
Ambient Air Temperature For Storage	-40...70 °C
Maximum Pressure	29 Pa flow rate 0 m³/h
Connections - Terminals	Cable
Ip Degree Of Protection	IP54
Device Composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Condition Of Use	Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Overfrequent filter replacement should be avoided Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly
-------------------------	---

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	12.5 cm
Package 1 Length	15.0 cm
Package 1 Weight	292.0 g
Unit Type Of Package 2	PAM
Number Of Units In Package 2	340
Package 2 Height	120 cm
Package 2 Width	100 cm
Package 2 Length	80 cm
Package 2 Weight	128 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)