

# Product datasheet

Specifications



Unika interlocked socket - 63 A -  
3P + N + E - 380...415 V AC - IP65  
- wall

PKB63P535

Price: 10,772.01 ZAR

## Main

|                           |                    |
|---------------------------|--------------------|
| Range                     | Mureva             |
| Product Or Component Type | Interlocked socket |
| Device Short Name         | Mureva socket      |
| Plug, Socket Category     | Low voltage        |
| Poles Description         | 3P + N + E         |
| Network Type              | AC                 |
| Outlet Standard           | Industrial         |

## Complementary

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Mounting Mode                  | Wall-mounted                                     |
| [In] Rated Current             | 63 A                                             |
| [Ue] Rated Operational Voltage | 380...415 V                                      |
| Network Frequency              | 50/60 Hz                                         |
| Ground Lug Clockwise Position  | 6 h                                              |
| Protection Type                | Without protection                               |
| Plug, Socket Material          | Housing: self-extinguishing polymer              |
| Contacts Material              | Pins: stainless steel<br>Screws: stainless steel |
| Connections - Terminals        | Captive screws                                   |
| Maximum Cable Cross Section    | 35 mm²                                           |
| Maximum Cable Outer Diameter   | 25 mm                                            |
| Cable Entry                    | Cable gland                                      |
| Thread Type                    | Pg 21                                            |
| Net Weight                     | 3 kg                                             |
| Base Dimension                 | 140 x 430 mm                                     |
| Height                         | 430 mm                                           |
| Width                          | 140 mm                                           |
| Depth                          | 190 mm                                           |
| Colour                         | Grey (RAL 7035)                                  |
| Voltage Colour                 | Red                                              |

## Environment

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                                 |
|---------------------------------------|-------------------------------------------------|
| Standards                             | IEC 60309-2<br>IEC 60309-1                      |
| Ip Degree Of Protection               | IP65 conforming to IEC 60529                    |
| Ik Degree Of Protection               | IK09 conforming to EN 62262                     |
| Fire Resistance                       | 750 °C conforming to IEC 60695-2-11             |
| Relative Humidity                     | 50 % at 40 °C<br>70 % at 30 °C<br>90 % at 20 °C |
| Ambient Air Temperature For Operation | 35 °C ( 86400 s )<br>-25...40 °C                |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type Of Package 1       | PCE        |
| Number Of Units In Package 1 | 1          |
| Package 1 Height             | 21.000 cm  |
| Package 1 Width              | 19.200 cm  |
| Package 1 Length             | 44.400 cm  |
| Package 1 Weight             | 2.858 kg   |
| Unit Type Of Package 2       | P12        |
| Number Of Units In Package 2 | 9          |
| Package 2 Height             | 34.000 cm  |
| Package 2 Width              | 80.000 cm  |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 37.722 kg  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Lower Impact Materials   Transparency   RoHS/REACH

Resource performance

 Minimum Percentage Of Recycled Plastic Content

58

Well-being performance

 Rohs Exemption Information

Yes

Certifications & Standards

|                          |                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                     |
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)                                                            |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                         |
| Circularity Profile      | No need of specific recycling operations                                                                              |