

Product datasheet

Specifications



PratiKa wander plug - straight - 32 A - 3P + E - 200...250 V AC - IP67

PKE32M724

⚠ Discontinued on: 30 Jun 2023

⚠ Discontinued

Main

| | |
|---------------------------|--------------|
| Range | PratiKa |
| Product Or Component Type | Wander plug |
| Device Short Name | PratiKa plug |
| Plug, Socket Category | Low voltage |
| Poles Description | 3P + E |
| Network Type | AC |
| Outlet Standard | Industrial |

Complementary

| | |
|-------------------------------------|---|
| Plug, Socket, Control Station Shape | Straight |
| [In] Rated Current | 32 A |
| [Ue] Rated Operational Voltage | 200...250 V |
| Network Frequency | 50/60 Hz |
| Ground Lug Clockwise Position | 9 h |
| Plug, Socket Material | Housing: self-extinguishing engineering polymer |
| Contacts Material | Sleeves: brass |
| Connections - Terminals | Captive screws |
| Cable Cross Section | 2.5...10 mm ² |
| Cable Outer Diameter | 11.5...21 mm |
| Cable Entry | Fair lead Cable gland |
| Thread Type | Pg 21 |
| Net Weight | 0.22 kg |
| Height | 152 mm |
| Width | 95 mm |
| Depth | 95 mm |
| Colour | Grey (RAL 7035) |
| Voltage Colour | Blue |

Environment

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| | |
|--|---|
| Standards | IEC 60309-2 IEC 60309-1 |
| Ip Degree Of Protection | IP67 conforming to IEC 60529 |
| Ik Degree Of Protection | IK08 conforming to EN 62262 |
| Fire Resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative Humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Operating Altitude | 2000 m |
| Ambient Air Temperature For Operation | 35 °C (86400 s) -25...40 °C |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 16 cm |
| Package 1 Width | 10 cm |
| Package 1 Length | 10 cm |
| Package 1 Weight | 264 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 6 |
| Package 2 Height | 17 cm |
| Package 2 Width | 26.3 cm |
| Package 2 Length | 27 cm |
| Package 2 Weight | 1.765 kg |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 12 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 4.017 kg |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Circularity Profile No need of specific recycling operations