

# Product datasheet

Specifications



## PratiKa socket - fast - angled - 16A - 2P + E - 200...250 V AC - panel

PKY16F723

**Price: 191.36 ZAR**

### Main

|                           |               |
|---------------------------|---------------|
| Range                     | Mureva        |
| Product Or Component Type | Socket        |
| Device Short Name         | Mureva socket |
| Plug, Socket Category     | Low voltage   |
| Poles Description         | 2P + E        |
| Network Type              | AC            |
| Outlet Standard           | Industrial    |

### Complementary

|                                     |   |
|-------------------------------------|---|
| Mounting Mode                       | Panel-mounted                                   |
| Plug, Socket, Control Station Shape | Angled  |
| [In] Rated Current                  | 16 A  |
| [Ue] Rated Operational Voltage      | 200...250 V                                     |
| Network Frequency                   | 50/60 Hz  |
| Ground Lug Clockwise Position       | 6 h   |
| Plug, Socket Material               | Housing: self-extinguishing engineering polymer |
| Contacts Material                   | Sleeves: brass                                  |
| Connections - Terminals             | Fast connection                                 |
| Cable Cross Section                 | 1...4 mm <sup>2</sup>                           |
| Net Weight                          | 0.147 kg  |
| Base Dimension                      | 65 x 85 mm                                      |
| Height                              | 85 mm   |
| Width                               | 73 mm   |
| Depth                               | 103 mm  |
| Colour                              | Grey (RAL 7035)                                 |
| Voltage Colour                      | Blue  |

### Environment

|                         |                              |
|-------------------------|------------------------------|
| Standards               | IEC 60309-2<br>IEC 60309-1   |
| Ip Degree Of Protection | IP67 conforming to IEC 60529 |
| Ik Degree Of Protection | IK08 conforming to EN 62262  |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

|  |   |
|--|---|
| <b>Fire Resistance</b>                       | 850 °C conforming to IEC 60695-2-1              |
| <b>Relative Humidity</b>                     | 50 % at 40 °C<br>70 % at 30 °C<br>90 % at 20 °C |
| <b>Ambient Air Temperature For Operation</b> | 35 °C ( 86400 s )                               |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type Of Package 1</b>       | PCE      |
| <b>Number Of Units In Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 9.5 cm   |
| <b>Package 1 Width</b>              | 6.5 cm   |
| <b>Package 1 Length</b>             | 8.2 cm   |
| <b>Package 1 Weight</b>             | 138.0 g  |
| <b>Unit Type Of Package 2</b>       | BB1      |
| <b>Number Of Units In Package 2</b> | 10       |
| <b>Package 2 Height</b>             | 12.0 cm  |
| <b>Package 2 Width</b>              | 26.0 cm  |
| <b>Package 2 Length</b>             | 26.7 cm  |
| <b>Package 2 Weight</b>             | 1.516 kg |
| <b>Unit Type Of Package 3</b>       | S03      |
| <b>Number Of Units In Package 3</b> | 30       |
| <b>Package 3 Height</b>             | 30.0 cm  |
| <b>Package 3 Width</b>              | 30.0 cm  |
| <b>Package 3 Length</b>             | 40.0 cm  |
| <b>Package 3 Weight</b>             | 5.1 kg   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations