

Product datasheet

Specifications



Harmony. Socket. for RPM3 power relays. 16 A screw clamp terminals. mixed contact

RPZF3

Price: 155.94 ZAR

Main

Range Of Product	Harmony Electromechanical Relays
Device Short Name	RPZ
Product Or Component Type	Socket
Product Compatibility	Plug-in relay RPM with 3 C/O contact
Contacts Type And Composition	3 C/O
[Ith] Conventional Free Air Thermal Current	16 A
[Ue] Rated Operational Voltage	< 250 V

Complementary

Shape Of Pin	Flat
Contact Terminal Arrangement	Mixed
Tightening Torque	< 1 N.m for M3.5 screw(s)
Fixing Mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)
[Uimp] Rated Impulse Withstand Voltage	4 kV
Overvoltage Category	III
Pollution Degree	3
Sale Per Indivisible Quantity	10
Width	40 mm
Net Weight	0.072 kg

Environment

Connections - Terminals	<ul style="list-style-type: none">- screw clamp terminals, flexible cable with cable end 1 x 0.5...1 x 2.5 mm² / AWG 20...AWG 14- screw clamp terminals, solid cable without cable end 1 x 0.5...1 x 1.5 mm² / AWG 20...AWG 16- screw clamp terminals, flexible cable with cable end 2 x 0.5...2 x 2.5 mm² / AWG 20...AWG 14- screw clamp terminals, solid cable without cable end 2 x 0.5...2 x 1.5 mm² / AWG 20...AWG 16
Ip Degree Of Protection	IP20 conforming to IEC 60529
Dielectric Strength	2500 V
Standards	IEC 61984
Product Certifications	CSA UL
Marking	CE

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Ambient Air Temperature For Storage	-40...85 °C
Ambient Air Temperature For Operation	-40...55 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	4.0 cm
Package 1 Length	8.5 cm
Package 1 Weight	77.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	6.3 cm
Package 2 Width	12 cm
Package 2 Length	20.2 cm
Package 2 Weight	770 g
Unit Type Of Package 3	S03
Number Of Units In Package 3	150
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	12.45 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee


The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

No need of specific recycling operations

Dimensions Drawings


Dimensions



- (1) Relays
- (2) Protection module
- (3) Maintaining clamp

Connections and Schema

Wiring Diagram



Symbols shown in blue correspond to Nema marking.