

# Product datasheet

Specifications



## Harmony. Bus jumper. 20 poles

RSLZ2



Price: 52.79 ZAR

### Main

|                               |                                                                |
|-------------------------------|----------------------------------------------------------------|
| Range Of Product              | Harmony Solid State Relays<br>Harmony Electromechanical Relays |
| Product Or Component Type     | Bus jumper                                                     |
| Sale Per Indivisible Quantity | 10                                                             |

### Complementary

|                                       |                                |
|---------------------------------------|--------------------------------|
| Accessory / Separate Part Category    | Connection accessory           |
| Product Compatibility                 | RSLZ - socket<br>SSLZ - socket |
| Ip Degree Of Protection               | IP00                           |
| Accessory / Separate Part Destination | Slim interface relay socket    |
| Net Weight                            | 0.003 kg                       |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 0.3 cm   |
| Package 1 Width              | 1.7 cm   |
| Package 1 Length             | 12.2 cm  |
| Package 1 Weight             | 8 g      |
| Unit Type Of Package 2       | BB1      |
| Number Of Units In Package 2 | 10       |
| Package 2 Height             | 2 cm     |
| Package 2 Width              | 6 cm     |
| Package 2 Length             | 13 cm    |
| Package 2 Weight             | 80 g     |
| Unit Type Of Package 3       | S03      |
| Number Of Units In Package 3 | 1000     |
| Package 3 Height             | 30 cm    |
| Package 3 Width              | 30 cm    |
| Package 3 Length             | 40 cm    |
| Package 3 Weight             | 8.497 kg |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓

Reach Free Of Svhc

✓

RoHS Exemption Information

Yes

## Certifications & Standards


|                          |                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                 |
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a>                                                            |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                     |
| Circularity Profile      | <a href="#">End of Life Information</a>                                                           |

Connections and Schema

Wiring Diagram


---

Side View - Coil Side



- (1) A1
- (2) A2
- (3) Bus jumper polarity A1
- (4) Bus jumper polarity A2

Side View - Contact Side



- (1) Do not exceed 2A max per relay when using RSLZ2 on the contact side