

Product datasheet

Specifications



Harmony. Solid state relay pre assembled. 2 A. random switching. spring sockets. input 16...30 V DC. output 24...250 V AC

SSL1A12BDRPR

Price: 610.42 ZAR

Main

Range Of Product	Harmony Solid State Relays
Product Or Component Type	Solid state relay up to 10 A
Device Short Name	SSL
Network Number Of Phases	1 phase
Output Switching Mode	Random voltage switching

Complementary

Mounting Support	Spring socket
[In] Rated Current	2 A
[Uc] Control Circuit Voltage	16...30 V DC
Clamping Force	10...40 N.m
Connections - Terminals	Flexible cable with cable end,clamping capacity: 0.2...1.5 mm² (AWG 24...AWG 16) Solid cable with cable end,clamping capacity: 0.2...1.5 mm² (AWG 24...AWG 16)
Capacitance Unbalance	1.5 pF input/output
Minimum Switching Voltage	16 V DC turn-on
Maximum Switching Voltage	5 V DC turn-off
Input Impedance	3.43 kOhm
Solid State Output Type	SCR output Random voltage switching
Load Current	0.07...2 A
Tansient Overvoltage	600 V AC
Surge Current	120 A for 16.6 ms 115 A for 20 ms
Maximum Voltage Drop	<1.1 V on-state
Maximum I²T For Fusing	285 A².s for 10 ms at 50 Hz 260 A².s for 8.3 ms at 60 Hz
Maximum Leakage Current	4 mA off-state
Dv/Dt	500 V/µs off-state at maximum voltage
Response Time	5 ms (turn-on) 10 ms (turn-off)
Overvoltage Category	III
Width	6.2 mm
Height	104.6 mm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	79.5 mm
Net Weight	0.0285 kg

Environment

Flame Retardance	V0 conforming to UL 94
Dielectric Strength	2500 V for input/output
Pollution Degree	2
Standards	IEC 60950-1 IEC 61000 IEC 62314 IEC 61984 EN 61984
Product Certifications	UL CSA CE UL 508 CSA22.2 No. 14-10 GOST
Marking	CURus CSA CE EAC
Ip Degree Of Protection	IP20
Ambient Air Temperature For Operation	-20...70 °C
Ambient Air Temperature For Storage	-20...85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.04 cm
Package 1 Width	0.625 cm
Package 1 Length	7.9 cm
Package 1 Weight	33.0 g

Contractual warranty

Warranty	18 Months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance


✓	Reach Free Of Svhc	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information


Dimensions Drawings

Dimensions



Performance Curves

Derating Curves



A : Load Current (Amperes)
B : Ambient Temperature (°C)