

Product datasheet

Specifications



basic analog output kit STB - +/- 10 V - 2 O - 9 bits + sign

STBAVO1265K

Price: 3,962.70 ZAR

Main

Range Of Product	Modicon STB distributed I/O solution
Product Or Component Type	Basic analog output kit
Kit Composition	STBAVO1265 module STBXTS2100, 6-terminal spring clamp connector STBXTS1100, 6-terminal screw type connector STBXBA1000 base
Analogue Output Type	Voltage: +/- 10 V
Analogue Output Number	2
Analogue Output Resolution	9 bits + sign

Complementary

Analogue Output Current	0.005 A
Response Time	3 ms
Cold Swapping	Yes
Hot Swapping	No for basic NIMs
Fallback	State 0
Data Format	IEC 61131-2 EN 61131-2
Update Time	25 ms
Protection Type	Short-circuit protection
Integral Linearity	+/- 0.1 %FS
Differential Linearity	Monotonic
Absolute Accuracy Error	+/- 0.5 % of full scale at 25 °C
Temperature Drift	+/-0.01 %/°C
Insulation Between Channels And Logic Bus	1500 V for 1 minute
Insulation Between Channels And Actuator Bus	30 V
Addressing Requirement	2 output words
Product Compatibility	Mounting base STBXBA1000 Power distribution module STBPDT3100/3105
[Us] Rated Supply Voltage	24 V DC
Supply	Power distribution module
Current Consumption	45 mA at 5 V DC for logic bus
Marking	CE

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overvoltage Category	II
Status Led	1 LED (green) module status (RDY)
Depth	70 mm
Height	13.9 mm
Width	128.3 mm
Net Weight	0.115 kg

Environment

Product Certifications	CSA FM Class 1 Division 2 UL
Pollution Degree	2 conforming to IEC 60664-1
Operating Altitude	<= 2000 m
Ip Degree Of Protection	IP20 conforming to IEC 61131-2 class 1
Ambient Air Temperature For Operation	0...60 °C (without)
Ambient Air Temperature For Operation	32...140 °F without
Ambient Air Temperature For Storage	-40...85 °C without
Ambient Air Temperature For Storage	-40...185 °F without
Relative Humidity	95 % at 60 °C without condensation
Vibration Resistance	3 gn at 58...150 Hz on 35 x 7.5 mm symmetrical DIN rail 5 gn at 58...150 Hz on 35 x 15 mm symmetrical DIN rail +/-0.35 mm at 10...58 Hz
Shock Resistance	30 gn for 11 ms conforming to IEC 88 reference 2-27

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.7 cm
Package 1 Width	8.0 cm
Package 1 Length	13.0 cm
Package 1 Weight	134.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	28
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.11 kg
Unit Type Of Package 3	PAL
Number Of Units In Package 3	448
Package 3 Height	60.0 cm
Package 3 Width	80.0 cm
Package 3 Length	448.0 cm

Package 3 Weight	60.032 kg
------------------	-----------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Dimensions




Connections and Schema


Wiring Diagrams

Examples

2 isolated analog actuators, external 24 VDC power supply



2 non-isolated analog actuators, 24 VDC supplied by the PDM



Pin	Top Connections	Bottom Connections
1	+24 VDC from the island's field power bus for field device accessories	+24 VDC from the island's field power bus for field device accessories
2	no connection	no connection

Pin	Top Connections	Bottom Connections
3	output to actuator 1	output to actuator 2
4	output channel return	output channel return
5	no connection	no connection
6	field power return (to the module)	field power return (to the module)