Product datasheet

Specifications



ConneXium Lite Managed Switch - 4 ports for copper

TCSESL043F23F0

Price: 4,789.50 ZAR

Main

Range Of Product	ConneXium
Product Or Component Type	Ethernet TCP/IP managed switch
Concept	Transparent Ready
Communication Port Protocol	Ethernet TCP/IP HTTP HTTPS SNMP LLDP
Port Ethernet	10/100BASE-TX - 4 port(s) copper cable
Maximum Number Of Switches In Cascade	Unlimited
Cybersecurity	Enable/disable communication ports

Complementary

Integrated Connection Type	Shielded RJ45 copper cable
Transmission Support Medium	Twisted shielded pairs cable CAT 5E for copper cable
Maximum Cable Distance Between Devices	100 m copper cable
Ethernet Service	Configuration via web server Multicast filtering Syslog SNMP-Traps
Communication Service	TFTP Port monitoring
Diagnostics Run Time	Log file
Maximum Number Of Switches In A Ring	50
Redundancy	RSTP
[Us] Rated Supply Voltage	12...24 V
Supply Voltage Limits	9.6…32 V DC SELV
Power Consumption In W	2.35 W
Electrical Connection	Removable connector 3 ways power supply
Mounting Support	35 mm symmetrical DIN rail
Marking	CE CULus RCM
Local Signalling	1 LED (green) for power supply 1 LED per channel (yellow) for data rate (ETH LINK) 1 LED per channel (green) for link status
Ethernet Cabling System	TF switches

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	25 mm
Height	114 mm
Depth	79 mm
Net Weight	0.103 kg

Environment

Ambient Air Temperature For Operation	0…60 °C
Relative Humidity	5…95 % non-condensing
Ip Degree Of Protection	IP30
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Standards	UL 61010
Product Certifications	CE UL RCM

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.600 cm
Package 1 Width	12.400 cm
Package 1 Length	17.600 cm
Package 1 Weight	167.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	28
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.161 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency



RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information