

Product datasheet

Specifications



Analogue input cartridge. Modicon M221. hoisting 2 analog I/O extension

TMC2HOIS01

Price: 2,542.68 ZAR

Main

Range Of Product	Modicon M221
Product Or Component Type	Analogue input cartridge
Product Specific Application	Hoisting applications
Product Compatibility	Modicon M221C
Analogue Input Number	2

Complementary

Analogue Input Type	current 4...20 mA current 0...20 mA voltage 0...10 V
Analogue Input Resolution	12 bits
Lsb Value	2.44 mV 0...10 Vvoltage 4.88 µA 0...20 mAcurrent 3.91 µA 4...20 mAcurrent
Conversion Time	20 ms
Sampling Duration	10 ms
Absolute Accuracy Error	+/- 0.1 % of full scale at 25 °C +/- 1 % of full scale
Temperature Drift	+/- 0.02 %FS/°C
Repeat Accuracy	+/- 0.5 %FS
Non-Linearity	+/- 0.01 %FS
Cross Talk	<= 1 LSB
Type Of Cable	Twisted shielded pairs cable
Electrical Connection	3 x 1.5 mm² 2 screw terminal blocks with pitch 3.81 mm adjustment for inputs
Maximum Cable Distance Between Devices	Twisted shielded pairs cable: <30 m for input
Insulation	Non-insulated between analogue input and internal logic
Height	41 mm
Depth	15 mm
Width	35 mm
Net Weight	0.015 kg
Permissible Continuous Overload	13 V, analogue input type: voltage 40 mA, analogue input type: current
Input Impedance	<= 250 Ohm current >= 1 MOhm voltage

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Immunity To Microbreaks	10 ms
-------------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	4.6 cm
Package 1 Length	7.0 cm
Package 1 Weight	20.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	75
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.305 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Toxic Heavy Metal Free	
✓ Mercury Free	
✓ Rohs Exemption Information	Yes
✓ Pvc Free	

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information