

Product datasheet

Specifications



CANopen cordset - molded female SUB-D9 connectors - standard - IP20 - UL - 0.3m

TSXCANCBDD03

⚠ Discontinued on: 30 Jun 2023

⚠ Discontinued

Main

Range Of Product	CANopen
Bus Type	CANopen
Accessory / Separate Part Categor	Connection accessories
Accessory / Separate Part Type	Connecting cable
Accessory / Separate Part Destination	CANopen bus
Cable Length	0.3 m

Complementary

Electrical Connection	2 female connectors SUB-D 9 pin(s)
Marking	CE
Net Weight	0.086 kg

Environment

Product Certifications	UL
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1 cm
Package 1 Width	15 cm
Package 1 Length	20 cm
Package 1 Weight	89 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	100
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	9.55 kg

Contractual warranty

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency

Well-being performance

✓ Toxic Heavy Metal Free	
✓ Mercury Free	
✓ Rohs Exemption Information	Yes
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations